



Core & Coil (71A) MH 175W - 450W

CORE & COIL HID MH BAL 175W M57 QUAD C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information				
ANSI Code	M57-M107			
Lamp Type	175/150W MH			
Number of Lamps	1 piece/unit			
Circuit Type	CWA			
Ballast Type	Magnetic HID			
Base Model	71A5590			
Core Size	3 X 4 (2 LW)			
Suitable For Outdoor Use	Yes			
Ignitor Catalog Number	NA			
Ignitor Temperature Rating	NA			
Capacitor Value	10 MFD			
Capacitor Catalog Number	7C100M40R			
Capacitor Requirements	400V			
Capacitor Temperature Rating	105°C			
Capacitor Diameter/Oval Dimensions	1.45 in			
Capacitor Height	3.75 in			
Automatic Restart	No			
Operating and Electrical				
Input Voltage	120/208/240/277 V			

Input Frequency	60 Hz				
Inp. Current (Open Circuit)	1.78/1.08/0.93/0.81 A				
Input Current (Starting)	1.26/0.7/0.61/0.53 A				
Input Current (Short Circuit)	1.06-1.59/0.6-0.9/0.52-0.78/0.45-0.67 A				
Secondary Short Circuit Current	1.5-1.9 A				
Constant Wattage Deviation	10%				
Ballast Factor (Nom)	1				
Power Factor (Nom)	0.90				
Nominal Open Circuit Voltage	305 V				
Input Current (Operating) (Nom)	1.8/1.04/0.9/0.8 A A				
Input Power (Nom)	210 W				
Rated Lamp Watts	175/150 W				
Wiring					
Wire Striplength	0.5 mm				
Wire Length by Color	12"				
Wire Type	Stranded				
Remote Wiring Configuration Allowed	Yes				
Max Ballast-Lamp Distance Remote	Determined by AWG used				
Wiring					


Datasheet, 2019, March 22 data subject to change

Core & Coil (71A) MH 175W - 450W

Recommended Fuse Value	5/3/3/2 A
Approval and Application	
Open Circuit Voltage Test (Volts)	275-335 V
Approbation Marks	ULR CSA certificate RoHS Compliant
Temperature Marking	C/D/D/D
UL Recognized	Yes
Hipot Test (1 Minute)	2000 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)
UL Temperature Code	1029D

Product Data	
Order product name	CORE & COIL HID MH BAL 175W M57 QUAD C&C
EAN/UPC - Product	781087097892
Order code	71A5590500D
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	913700572909
Net Weight (Piece)	3.217 kg

Dimensional drawing



MH BAL 175W M57 QUAD C&C

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID MH BAL 175W M57	3.95 in	2.42 in	3.9 in	3.5 in	2.8 in	2.4 in
QUAD C&C						

