

CRS8

Quick Release 8W LED Gravity-Fit Pendants

Specifications/Features

Fixture

High performance, eco-friendly 8W LED pendant delivering 750+ lumens; matching the output and uniformity of a 50W T4 Halogen, while only consuming 7.3W, and achieving an efficacy of over 100 lumens/watt. Omni-directional light output provides even illumination of the shade, as well as a strong downward punch of light; providing functional task illumination.

Available in four (4) standard lengths (24", 48", 72", and 96") eliminating the need for field adjustment. For installations requiring a custom length, the pendant is easily field adjustable.

Must be used with one of the mounting options listed below. Choose from line voltage track, line voltage flexible track or canopy mounting options (details below).

Dimming allows smooth illumination down to 10%.

Compatible with Gravity-Fit Decorative Shades. Shade options include hand crafted glass, case glass, fabric, and metal (shades sold separately).

A frosted diffusion lens is included.

Lamp/Electrical

The 8W LED pendant includes six (6) LED Arrays with twenty-six (26) total LEDs achieving an efficacy of over 93 lumens/watt.

Available in 3000K, CRI 80min., 83 typical. High CRI version also available.

Excellent fixture to fixture color consistency within a 4-step MacAdam Ellipse tolerance.

System designed and rated for 50,000 hours at 70% lumen maintenance.

Driver

Triac Dimming Driver: Input Wattage 8W; Input Voltage 120VAC, 50/60Hz 0-10V Dimming Driver: Input Wattage 8W; Input Voltage 120/277VAC, 50/60Hz

Warrantv

Fixture is covered by ConTech's full five (5) year replacement guarantee after date of purchase.

Labels/Usage

CSA Certified to UL Standards. High CRI version T24 High Efficacy Compliant. Suitable for dry locations.

Туре	
Project	
	24" - 96
For compatible shades, see attached Gravity Fit Decorative Shade Options	4" 5

1-5/8

Catalog No..



CRS8

Quick Release 8W LED Gravity-Fit Pendants

Catalog No)	

Гуре ______

Project _____

Mounting Options



Line Voltage Track Adapter

To connect pendant to standard line voltage track. Triac LED dimming driver included. 7" L x 2" H. Black, white and silver finish only.

CRS8-LVTQRD1-(B,P,S) - Triac Dimming Driver



Decorative Ceiling Canopy

Mounts to NEC approved 4" round or octagon junction box with minimum depth of 1-1/2". 0-10V LED Dimming driver included. 2-1/2" H, 4-3/8" Dia.

CRS8-DQRCD1-(AB,B,P,S) - Triac Dimming Driver CRS8-DQRCD2-(AB,B,P,S) - 0-10V Dimming Driver



Odyssey Line Voltage Flexible Track Adapter

To connect pendant to Odyssey line voltage flexible track. Triac LED dimming driver included. 6" L x 3-1/2" H. Antique bronze and silver finish only.

CRS8-ODYQRD1-(AB,S) - Triac Dimming Driver



Thin Ceiling Canopy

Mounts to NEC approved 4" round or octagon junction box with minimum depth of 1-1/2". 0-10V LED Dimming driver included. 1/4" H, 4-3/8" Dia.

CRS8-TQRCD1-(AB,B,P,S) - Triac Dimming Driver CRS8-TQRCD2-(AB,B,P,S) - 0-10V Dimming Driver



Three Pendant Ceiling Canopy

Mounts to NEC approved 4" round or octagon junction box with minimum depth of 1-1/2". 0-10V LED Dimming driver included. 2" H x 12" Dia.

CRS8-3QRCD1-(AB,B,P,S) - Triac Dimming Driver CRS8-3QRCD2-(AB,B,P,S) - 0-10V Dimming Driver



Ceiling Canopy

LED Dimming driver included. 1-5/16" H, 4-3/8" Dia.

CRS8-QRCD1-(AB,B,P,S) - Triac Dimming Driver CRS8-QRCD2-(AB,B,P,S) - 0-10V Dimming Driver

Ordering Information

Example Order:	CRS84830K -	S CRS8	-QRCD2 - S	
Fixture	Color Temp*	Finish	Mounting Option	Finish
CRS824 - 2' Pendant CRS848 - 4' Pendant CRS872 - 6' Pendant CRS896 - 8' Pendant	80 CRI	AB - Antique Bronze/ Black Cable B - Black/ Black Cable P - White/ Transparent Cable S - Silver/ Transparent Cable	CRS8-LVTQRD1 - Line Voltage Track Adapter, Triac Dimming (B,P,S only) CRS8-ODYQRD1 - Odyssey Line Voltage Flexible Track Adapter, Triac Dimming (AB,S only) CRS8-DQRCD1 - Decorative Ceiling Canopy, Triac Dimming CRS8-TQRCD1 - Thin Ceiling Canopy, Triac Dimming CRS8-QRCD1 - CRS8-QRCD1 - Ceiling Canopy, Triac Dimming CRS8-QRCD2 - Ceiling Canopy, Triac Dimming CRS8-3QRCD1 - Three Pendant Canopy, Triac Dimming CRS8-3QRCD2 - Three Pendant Canopy, 0-10V Dimming CRS8-3QRCD2 - Three Pendant Canopy, 0-10V Dimming	AB - Antique Bronze B - Black P - White S - Silver Order Shades Separately

^{*}Consult Factory for additional color temperatures 1. T24 High Efficacy Compliant

Hand Crafted Gravity Fit Glass Shades

- Multiple layers of clear and colored glass are combined to create color effects not found in typical factory glass
- Special glass blowing techniques create air bubbles and unique variations in the color and thickness of the glass, giving each shade a distinct, artisan appearance
- Each shade is available in four (4) standard finishes:









Pineapple Twist

Fabric Shades

- Available in three (3) Square, Drum and Cylinder shapes with six (6) standard fabrics
- Optional top dust cover and acrylic bottom diffuser (may only be used with CRS8 pendant; consult factory for use on Symphony LED pendant)
- Custom shade sizes and fabrics are available, consult factory for information







RCG565 - Tortoise Shell

RCG675 - Pineapple Twist RCG785 - Blue Optic Swirl



6" High x 6-5/8" Diameter

RCG122 - Optic Swirl RCG562 - Tortoise Shell RCG672 - Pineapple Twist RCG782 - Blue Optic Swirl



5" High x 5-1/2" Diameter

RCG129 - Optic Swirl RCG569 - Tortoise Shell RCG679 - Pineapple Twist RCG789 - Blue Optic Swirl



9" High x 6-1/2" Diameter

RCG126 - Optic Swirl RCG566 - Tortoise Shell RCG676 - Pineapple Twist RCG786 - Blue Optic Swirl




6" High x 5-5/8" Diameter

RCG128 - Optic Swirl RCG568 - Tortoise Shell RCG678 - Pineapple Twist RCG788 - Blue Optic Swirl

www.contechlighting.com








DECORATIVE GRAVITY FIT PENDANT SHADES

Designer Series

Available in three (3) shapes with seven (7) standard finishes



Large Globe



Small Globe



Jar



- · Gravity fit shade made of case glass
- 5-3/4" Diameter x 6" High

CTG112 - Smoke Gray Crackle CTG111 - Champagne Crackle CTG122 - Smoke Gray Seeded CTG121 - Champagne Seeded CTG132 - Smoke Gray CTG134 - Frosted White CTG131 - Champagne

Double Cylinder



Inner Shade Series

CTG 434 - Frosted White

516 - Gray Crackle 527 - Champ. Seeded 517 - Champ. Crackle 515 - Clear Crackle

526 - Gray Seeded 525 - Clear Seeded

Elements Metallic Glass Cylinder



G - Gold S - Silver/


Chrome

DECORATIVE GRAVITY FIT PENDANT SHADES






Gravity fit shade made of case glass • 8" High x 4-1/4" Diameter · Available in Amber, Blue, Red, and White



W - White





B - Blue



www.contechlighting.com





DECORATIVE GRAVITY FIT PENDANT SHADES



Bullet · Gravity fit shade made of case glass • 10-1/8" High x 4-3/4" Diameter Available in White Frost, Blueberry, Mango Sunset, Amber, and Red White Blueberry Mango Amber Red Sunset Frost Shade OFG301 - White Frost OFG307 - Amber OFG308 - Red OFG302 - Blueberry OFG303 - Mango Sunset

Flat Metal Cone





Bell



OFG101 - White Frost OFG102 - Blueberry OFG103 - Mango Sunset OFG103 - Amber OFG108 - Red

Luminous Wrap

- Gravity fit shade made of Parchment Paper or Frosted Plastic
- Includes brass ring mount; optional chrome external hardware is available (MLA248-CHR NUTS)
- 10" High x 4-1/2" Diameter
- Available in Beige Parchment Paper and Natural Tan Parchment Paper



MLA248

B - Beige Parchment PaperN - Natural Parchment Paper



OFG201 - White Frost OFG202 - Blueberry OFG203 - Mango Sunset

OFG207 - Amber OFG208 - Red

1-847-559-5500



CRS8

Quick Release 8W LED Gravity-Fit Pendants

Catalog No	


Project __


CRS8**30KW

Designed for 50,000 Hour Lamp Life¹; LM-63 Test No. 81642

Light Output (Fixture Delivered Lumens): 732 Total Watts@120V: 7.35 Lumens Per Watt: 100 Color Rendering Index (CRI)2: 84

Color Temperature (CCT)3: 3013K Warm White Spectral Power Distribution Chart⁴





Candlepower Summary		
FROM 0	CANDELA	LUMENS
0	91	
5	91	9
15	96	27
25	99	46
35	100	63
45	97	76
55	91	82
65	81	81
75	69	73
85	57	62
95	53	56

Intensity Distribution			
DISTANCE (FT.)	FOOTCANDLES (FC)	BEAM DIAMETER (FT.)	
6'	2.5	9.9	
8'	1.4	13.2	
10'	0.9	16.6	
12'	0.6	19.9	
14'	0.5	23.2	
16' /	0.4	26.5	

^{1.} Accuracy of rendering colors