

SPECIFICATION SHEET: WH5-277-L

This Is An Original Product From Fulham Co., Inc

Description : WorkHorse Series Versatile, Solid State Electronic Ballast. Small Case Size,


High Power Factor, Light Weight, Available In 120/230/277V 50/60 Hz.

This Ballast Will Operate Following Lamps.

REFER TO LAMP WATTS/TYPE

ELECTRICAL DATA (277 VOLT APPLICATION)

INPUT VOLT: 277V ± 10%	, 50/60Hz								
LAMP WATTS/TYPE	LAMPS OPERATED	INPUT WATTS	LINE CURRENT	BALLAST FACTOR	EFFICACY FACTOR				
F54T5HO	2	110	0.43	0.91	0.83				
CFQ18W	4	78	0.31	1.01	1.29				
CR55WT5	2	98	0.38	0.82	0.84				
FT40W	2	84	0.33	0.91	1.09				
FT40W	3	113	0.43	0.83	0.73				
CFTR42W	2	81	0.31	0.85	1.05				
POWER FACTOR		/	> 0.9						
THD			< 35 %						
EMI/RFI COMPLIANCE	FCC PART 18-A								
SOUND RATING	17		"A"						
BALLAST TYPE		INSTANT START							
VOLTAGE TRANSIENTS	/	ANSI C82.11 - 1993							
INPUT/PROTECTION			FUSE						
OUTPUT/PROTECTION			-						
MIN. OPERATING TEMP	- 30 °C ('- 20 °F)								
MAX. CASE TEMP	70 °C (158 °F)								
APPROVALS/CLASS	UL LISTED, CLASS " P ", 1 OUTDOOR								
APPROVALS/CLASS	* UL /cUL LISTED, CLASS " P ", 1 OUTDOOR								



WIRING DIAGRAMS								
WIRE	BLACK	WHITE	RED	BLUE	YELLOW	BROWN		
LENGTH - INCHES	12 <u>+</u> 1"	12 <u>+</u> 1"	36 <u>+</u> 1"	-	36 <u>+</u> 1"	-		

WIRING DIAGRAMS DEPENDS ON THE LAMP TYPE. PLEASE REFER TO FULHAM'S CATALOG.

NOTE : This Ballast Must Be Grounded

Fulham Co., Inc extends limited warranty only to the original purchaser or to the first user for the period of <u>5 years</u> from the date of manufacture as indicated by the date code stamped on each product and when properly installed and under normal conditions of use. For additional warranty guide line, please refer to our Complete Product Catalog OR <u>call Customer Service at 1-323-599-5000</u>.

DUE TO A PROGRAM OF CONTINUOUS IMPROVEMENT, FULHAM Co., INC RESERVES THE RIGHT TO MAKE ANY VARIATION IN DESIGN OR CONSTRUCTION TO THE EQUIPMENT DESCRIBED.



SPECIFICATION SHEET: WH5-277-L

This Is An Original Product From Fulham Co., Inc

Description: WorkHorse Series Versatile, Solid State Electronic Ballast. Small Case Size,


High Power Factor, Light Weight, Available In 120/230/277V 50/60 Hz.

This Ballast Will Operate Following Lamps.

REFER TO LAMP WATTS/TYPE

ELECTRICAL DATA (277 VOLT APPLICATION)

INPUT VOLT: 277V ± 10%,	50/60Hz							
LAMP WATTS/TYPE	LAMPS OPERATED	INPUT WATTS	LINE CURRENT	BALLAST FACTOR	EFFICACY FACTOR			
F39T5HO	2	74	0.29	0.88	1.20			
FT50W	2	112	0.43	1.00	0.89			
FT50W	1	49	0.19	0.81	1.64			
* F60T12	1	49	0.19	0.81	1.64			
* F20T12	2	39	0.15	0.84	2.15			
* F20T12	1	25	0.10	0.90	3.58			
POWER FACTOR		<u>, </u>	> 0.9					
THD			< 35 %					
EMI/RFI COMPLIANCE	FCC PART 18-A							
SOUND RATING	1		"A"					
BALLAST TYPE		2	INSTANT START					
VOLTAGE TRANSIENTS	/		ANSI C82.11 - 1993					
INPUT/PROTECTION		FUSE						
OUTPUT/PROTECTION			-					
MIN. OPERATING TEMP	- 30 °C ('- 20 °F)							
MAX. CASE TEMP			70 °C (158 °F)					
APPROVALS/CLASS	UL LISTED, CLASS " P ", 1 OUTDOOR							
APPROVALS/CLASS	* UL /cUL LISTED, CLASS " P ", 1 OUTDOOR							



WIRING DIAGRAMS								
WIRE	BLACK	WHITE	RED	BLUE	YELLOW	BROWN		
LENGTH - INCHES	12 <u>+</u> 1"	12 <u>+</u> 1"	36 <u>+</u> 1"	-	36 <u>+</u> 1"	-		

WIRING DIAGRAMS DEPENDS ON THE LAMP TYPE. PLEASE REFER TO FULHAM'S CATALOG.

NOTE : This Ballast Must Be Grounded

Fulham Co., Inc extends limited warranty only to the original purchaser or to the first user for the period of <u>5 years</u> from the date of manufacture as indicated by the date code stamped on each product and when properly installed and under normal conditions of use. For additional warranty guide line, please refer to our Complete Product Catalog OR <u>call Customer Service at 1-323-599-5000</u>.

DUE TO A PROGRAM OF CONTINUOUS IMPROVEMENT, FULHAM Co., INC RESERVES THE RIGHT TO MAKE ANY VARIATION IN DESIGN OR CONSTRUCTION TO THE EQUIPMENT DESCRIBED.



SPECIFICATION SHEET: WH5-277-L

This Is An Original Product From Fulham Co., Inc

Description: WorkHorse Series Versatile, Solid State Electronic Ballast. Small Case Size,


High Power Factor, Light Weight, Available In 120/230/277V 50/60 Hz.

This Ballast Will Operate Following Lamps.

REFER TO LAMP WATTS/TYPE

ELECTRICAL DATA (277 VOLT APPLICATION)

INPUT VOLT: 277V ± 10%,	50/60Hz							
LAMP WATTS/TYPE	LAMPS OPERATED	INPUT WATTS	LINE CURRENT	BALLAST FACTOR	EFFICACY FACTOR			
* F32T8	3	104	0.40	1.09	1.06			
* F48T8HO	2	103	0.40	1.10	1.07			
		4						
	4	<u> </u>		<u>l</u>	<u> </u>			
POWER FACTOR			> 0.9					
THD			< 35 %					
EMI/RFI COMPLIANCE			FCC PART 18-A					
SOUND RATING	1		"A"					
BALLAST TYPE		1	INSTANT START					
VOLTAGE TRANSIENTS		ANSI C82.11 - 1993						
INPUT/PROTECTION	FUSE							
OUTPUT/PROTECTION			-					
MIN. OPERATING TEMP	$-30^{0}\text{C}('\text{-}20^{0}\text{F})$							
MAX. CASE TEMP			70 °C (158 °F)					
APPROVALS/CLASS	UL LISTED, CLASS " P ", 1 OUTDOOR							
APPROVALS/CLASS	* UL /cUL LISTED, CLASS " P ", 1 OUTDOOR							



WIRING DIAGRAMS								
WIRE	BLACK	WHITE	RED	BLUE	YELLOW	BROWN		
LENGTH - INCHES	12 <u>+</u> 1"	12 <u>+</u> 1"	36 <u>+</u> 1"	-	36 <u>+</u> 1"	-		

WIRING DIAGRAMS DEPENDS ON THE LAMP TYPE. PLEASE REFER TO FULHAM'S CATALOG.

NOTE: This Ballast Must Be Grounded

Fulham Co., Inc extends limited warranty only to the original purchaser or to the first user for the period of 5 years from the date of manufacture as indicated by the date code stamped on each product and when properly installed and under normal conditions of use. For additional warranty guide line, please refer to our Complete Product Catalog OR <u>call Customer Service at 1-323-599-5000</u>.

DUE TO A PROGRAM OF CONTINUOUS IMPROVEMENT, FULHAM Co., INC RESERVES THE RIGHT TO MAKE ANY VARIATION IN DESIGN OR CONSTRUCTION TO THE EQUIPMENT DESCRIBED.