



SC: 10" Glass Reflector
Closed Housing - Designer Red finish



SOL: 10" Glass Reflector
Open Housing - Standard Brite Plate finish



SOR: 10" Glass Reflector
Open Housing - Designer Royal Blue finish

Description

The Simcoe™ luminaire is an excellent choice for the designer who desires the ability to choose a luminaire's style, color and overall appearance, then combine it with leading edge optical assemblies. Featuring fully closed or slotted top decorative domes and the choice of trim levels, Simcoe™ can be styled to match the building décor.

Features

Functional Retro-look For applications with functional décor • Customize the look with color and accessories

Mount 1/2" and 3/4" hub for rigid pendant • Cable suspension • Hang straight stems

Construction Steel housing and bottom ring • Wire support rods

Optics Prismatic borosilicate glass reflector

Finish Standard, bright plate finish

• Designer colors can be specified

EISA & Pulse Start Metal Halide AccuLite 150W Pulse Start MH luminaires with electronic ballast are designed and built to EISA standards • Pulse Start provides longer lamp life, more lumens per watt, better lumen maintenance, superior color rendering, faster lamp warm up and faster hot restrike • For more information on EISA see page 516

Lampholder HID - specification grade porcelain, medium base • Open HID fixtures are supplied with a lampholder for use open rated metal halide lamps • CFL - 4 pin GX24Q base


Ballast Remote ballast – order separately • See ballast page for maximum allowable lamp to ballast distance

Listing UL1598/CSA C22.2 250

• Suitable for damp locations

Dimensions

Series	Dia.	H
SO, SC	10 1/2"	11"
SOL, SCL	12"	11 1/2"
SOR, SCR	12"	11 1/2"



Ordering Information Example: SCR70PS-G10-GP-WH

Series	Lamp (Watts/Type)	Ballast	Reflector	Trim & Lenses	Housing Color	Mounting
SCR	70PS	-	-G10	-GP	-WH	-
Closed Top Housing SC With reflector only SCL With reflector and bottom ring SCR With reflector, rods and bottom ring Open Top Housing SO With reflector only SOL With reflector and bottom ring SOR With reflector, rods and bottom ring	● Pulse Start Metal Halide† Open fixtures furnished with ANSI Type "O" lamp holder ED17 - Medium base 50PS, 70PS, 100PS, § © { 150PS Probe Start Metal Halide† Open fixtures furnished with ANSI Type "O" lamp holder BD17 - Medium base § { 175MH ● Compact Fluorescent GX24Q base 126CF, 132CF, 142CF, 157CF Incandescent Medium base 150IN, 300IN	REMOTE BALLAST ‡ Order separately	Glass - G10 10" Dia. Borosilicate glass	No Trim No Suffix Bottom Closure Tempered glass Available with SCR & SOR models only - G Clear - GP Prismatic Louver Available with SCR & SOR models only Not available with lens - V Brite-Plate™ - V - color Specify color (polyester powder coat finish)	Housing and Ring No Suffix Brite Plate™ -WH White -BL Black Designer Colors Consult Factory	Stem No Suffix Hub for use with 1/2" or 3/4" stem Cable Suspension -CS Provision for Cable Suspension (Incandescent lamps only, order kit separately)

Commercial & Retail

Accessories

Accessories are ordered and shipped separately

Description	Catalog #
Cable Suspension Kits - order separately from page 605 Not suitable for CFL fixtures	
Hang Straight Kits - order separately from page 605	

† **Metal Halide:**

© EISA -Pulse Start MH: 150W - 150W with electronic ballast meets EISA requirements.

NEC compliance: Pulse Start & Probe Start MH luminaires are furnished with a lampholder for use with an open rated (protected) lamp, ANSI Type 'O'.

‡ **Lamp Socket Protector:**

Required in Canada when using 208V, 240V & 480V - add suffix "-LSP."

§ **Not for use in the United States.**

● Fixtures are **ENERGY EFFICIENT**.

