

# JUNO HD COMMERCIAL TRAC

1 20V, 2-Circuit/2-Neutral Trac System

## TRAC SECTIONS, JOINERS, FEEDS, ACCESSORIES & FIXTURES

### TEK Series

#### SYSTEM COMPONENTS



**TEK11-BL, TEK11-WH**  
End Feed - Left Polarity  
Enables feeding of TEK Trac from top.  
Use as Conduit End Feed also.



**TEK24-BL, TEK24-WH**  
Adjustable Connector  
Capable of joining two TEK Trac sections at 90° to 180°. Ideal for applications where using an "L" connector is not practical; also useful for installing Trac around curved architectural details.



**SKB10-BL, SKB10-WH**  
Mounting Bracket  
For mounting direct to ceiling



**TEK12-BL, TEK12-WH**  
End Feed - Right Polarity  
Enables feeding of TEK Trac from top.  
Use as Conduit End Feed also.



**TEK34-BL, TEK34-WH**  
90° "L" Connector  
Joins TEK Trac sections to make a 90° angle with continued electrical feed. May be used to feed TEK Trac from top.



**SKBT12-BL, SKBT12-WH**  
Mounting Bracket  
For mounting to flush tile T-bar ceiling.



**TEK11CL-BL, TEK11CL-WH**  
Current Limiting End Feed - Left Polarity  
Enables feeding of TEK Trac from top. Requires two TEKCL Current Limiters (one per circuit) to provide trac current limiting per national, state and local energy codes.



**TEK38-BL, TEK38-WH**  
"X" Connector  
Joins four TEK Trac sections to make an "X" intersection with continued electrical feed. May be used to feed TEK Trac from top.



**SKBX12-BL, SKBX12-WH**  
Mounting Bracket  
For mounting to drop tile recessed T-bar ceiling.



**TEK12CL-BL, TEK12CL-WH**  
Current Limiting End Feed - Right Polarity  
Enables feeding of TEK Trac from top. Requires two TEKCL Current Limiters (one per circuit) to provide trac current limiting per national, state and local energy codes.



**TEK39-BL, TEK39-WH**  
"T" Connector - Adjustable Right Polarity  
Joins three TEK Trac sections to make a "T" intersection with continued electrical feed. May be used to feed TEK Trac from top.



**SKB30-BL, SKB30-WH**  
Ceiling Cup Kit  
Use to suspend TEK Trac from the ceiling when using steel cable or threaded rod. Included bracket provides suspension attachment point and ceiling cup covers the bracket for an aesthetically pleasing result. Combine with SP4P and SKB34 or 1/4"-20 threaded rod (supplied by others) for a complete suspension solution.



**TCL0.5BL, TCL0.5WH, TCL1BL, TCL1WH, TCL2BL, TCL2WH, TCL3BL, TCL3WH, TCL4BL, TCL4WH, TCL5BL, TCL5WH, TCL6BL, TCL6WH, TCL7BL, TCL7WH, TCL8BL, TCL8WH, TCL9BL, TCL9WH, TCL10BL, TCL10WH, TCL12BL, TCL12WH, TCL14BL, TCL14WH**  
Plug-In Current Limiters  
For use with TEK11 or TEK12 Current Limiting End Feeds. Available in 0.5A (60W), 1A (120W), 2A (240W), 3A (360W), 4A (480W), 5A (600W), 6A (720W), 7A (840W), 8A (960W), 9A (1080W), 10A (1200W), 12A (1440W) and 14A (1680W) ratings.



**TEK40-BL, TEK40-WH**  
"T" Connector - Adjustable Left Polarity  
Joins three TEK Trac sections to make a "T" intersection with continued electrical feed. May be used to feed TEK Trac from top.



**SKB34-5, SKB34-9**  
Cable Suspension Kit  
Use to suspend TEK Trac from the ceiling with supplied 5' or 9' steel cable. Includes cable and cable adjustment fitter. Combine with SP4P and SKB30 for a complete suspension solution.



**GES15-BL, GES15-WH**  
Outlet Box Cover  
Thermoplastic outlet box cover for use when feeding TEK Trac directly over outlet box using TEK11, TEK12, TEK14, TEK34, TEK38, TEK39 or TEK40.



**SPUS12-BL, SPUS12-WH, SPUS18-BL, SPUS18-WH, SPUS24-BL, SPUS24-WH, SPUS48-BL, SPUS48-WH**  
Mounting Stem Kit  
Use to suspend TEK Trac from the ceiling. Combine with SP4P for suspension-only points. Available in 12", 18", 24" and 48" lengths.



**TEK14-BL, TEK14-WH**  
Center Feed  
Joins two TEK trac sections in-line both electrically and mechanically. Enables feeding of TEK Trac from top at intersection.



**TEK41-BL, TEK41-WH**  
Dead End  
Not supplied with TEK Trac sections - must be ordered separately.



**TEK21-BL, TEK21-WH**  
Miniature Straight Connector  
Joins two TEK trac sections in-line both electrically and mechanically.



**XTSV12**  
Trac Conductor Bending Tool  
All-in-one hand tool bends the trac conductors and measures the correct length to ensure proper electrical contact. Required only if trac sections are cut in the field.



**SP4P-BL, SP4P-WH**  
Universal Suspension Coupler  
Use with SPUS Stem Kit or SKB34 Cable Kit or 1/4"-20 threaded rod (supplied by others) to suspend TEK Trac except at feed or connection points.

Finishes: BL - Black, WH - White



1300 S. Wolf Road • Des Plaines, IL 60018 • Phone (847) 827-9880 • Fax (847) 827-2925  
220 Chrysler Drive • Brampton, Ontario • Canada L6S 6B6 • Phone (905) 792-7335 • Fax (905) 792-0064  
Visit us at [www.junolightinggroup.com](http://www.junolightinggroup.com)

Printed in U.S.A. ©2014 Juno Lighting, LLC.