



TRAC 12

Miniature Low Voltage Trac System

12V ELECTRONIC TRANSFORMERS

**TL544 LED, TL546, TL547,
TL548 LED, TL566 LED, TL567 LED**

Project: _____

Fixture Type: _____

Location: _____

Contact/Phone: _____


PRODUCT SPECIFICATIONS

Catalog Number TL544 LED 60W 120 12AC 6CP BL, TL544 LED 60W 120 12AC 6CP WH

Description Trac 12V AC 60-Watt LED Compatible Surface Mount Transformer • Low profile 12 volt electronic transformer • Rated for 0-60 watts for LED or incandescent loads • 6' three-wire cord set and 4 1/2" leads with mating connector for TL43 monopoint • Rocker on/off switch • Automatic resetting thermal, overload and short circuit protection.

Labels ETL Listed for use in the U.S. (UL 2108) and Canada (CSA C22.2 No. 9).

Surface Mount Transformer




Note: Remoting more than 5' is not recommended due to voltage drop.

Catalog Number TL546 150W 120 12AC BL, TL546 150W 120 12AC WH

Description Trac 12V AC 150-Watt Canopy Transformer (Incandescent only) • Low profile 12 volt electronic transformer • Rated for 10-60 watts for incandescent loads • 6' three-wire cord set and 4 1/2" leads with mating connector for TL43 monopoint • Rocker on/off switch • Automatic resetting thermal, overload and short circuit protection.

Labels UL listed, CSA certified.

Canopy Transformer



Note: Remoting more than 5' is not recommended due to voltage drop.

Catalog Number TL566 LED 100W 120 12AC BL, TL566 LED 100W 120 12AC WH

Description Trac 12V AC 100-Watt LED Compatible Canopy Transformer • Canopy with 12 volt electronic transformer mounts over 120 volt outlet box to end-feed one Trac section or center feed two Trac sections • Rated for 0-100 watts for LED or incandescent loads • Supplied with mounting plate • Automatic resetting thermal, overload and short circuit protection • Not designed for use with Trac 12/25 trac.

Labels ETL Listed for use in the U.S. (UL 2108) and Canada (CSA C22.2 No. 9).


Note: Remoting more than 5' is not recommended due to voltage drop.

Catalog Number TL547 150W 120 12AC BL, TL547 150W 120 12AC WH

Description Trac 12V 150-Watt Surface Transformer (Incandescent only) • 12 volt electronic transformer • Rated for 50-150 watts for incandescent loads • For in-line (Trac 12 trac only) or remote installation up to 5' away (Trac 12 or Trac 12/25) • End or top feed supply wiring using 1/2" electrical connectors • On/off switch • Automatic resetting thermal, overload and short circuit protection.

Labels UL listed, CSA certified.

Surface Transformer



Note: Remoting more than 5' is not recommended due to voltage drop.

Catalog Number TL567 LED 100W 120 12AC BL, TL567 LED 100W 120 12AC WH

Description Trac 12V AC 100-Watt LED Compatible Surface Transformer • 12 volt electronic transformer • Rated for 0-100 watts for LED or incandescent loads • For in-line (Trac 12 trac only) or remote installation up to 5' away (Trac 12 or Trac 12/25) • End or top feed supply wiring using 1/2" electrical connectors • On/off switch • Automatic resetting thermal, overload and short circuit protection.

Labels ETL Listed for use in the U.S. (UL 2108) and Canada (CSA C22.2 No. 9).


Note: Remoting more than 5' is not recommended due to voltage drop.

Catalog Number TL548 LED 60W 120 12AC BL, TL548 LED 60W 120 12AC WH

Description Trac 12V AC 60-Watt LED Compatible Plug-In Electronic Transformer • Rated for 0.5-60 watts for LED or incandescent loads • Includes 10' two-wire cord • Integral on/off switch • Automatic resetting thermal, overload and short circuit protection • May also be used with Trac12/25 trac.

Labels UL listed, CSA certified.

Portable Plug-In Transformer



Specifications subject to change without notice.

TRAC 12

Miniature Low Voltage Trac System

12V ELECTRONIC TRANSFORMERS

**TL544 LED, TL546, TL547,
TL548 LED, TL566 LED, TL567 LED**

PRODUCT CODES

| Catalog Number | Finish | Description |
|--------------------------------------|--------|--|
| TL544 LED 60W 120 12AC 6CP WH | White | 60W LED-Compatible Electronic Surface Mount 12V Transformer |
| TL544 LED 60W 120 12AC 6CP BL | Black | 60W LED-Compatible Electronic Surface Mount 12V Transformer |
| TL546 150W 120 12AC WH | White | 150W Electronic Canopy Mount 12V Transformer |
| TL546 150W 120 12AC BL | Black | 150W Electronic Canopy Mount 12V Transformer |
| TL566 LED 100W 120 12AC WH | White | 100W LED-Compatible Electronic Canopy Mount 12V Transformer |
| TL566 LED 100W 120 12AC BL | Black | 100W LED-Compatible Electronic Canopy Mount 12V Transformer |
| TL547 150W 120 12AC WH | White | 150W Electronic Surface Mount 12V Transformer |
| TL547 150W 120 12AC BL | Black | 150W Electronic Surface Mount 12V Transformer |
| TL567 LED 100W 120 12AC WH | White | 100W LED-Compatible Electronic Surface Mount 12V Transformer |
| TL567 LED 100W 120 12AC BL | Black | 100W LED-Compatible Electronic Surface Mount 12V Transformer |
| TL548 LED 60W 120 12AC WH | White | 60W LED-Compatible Electronic Portable Plug-in 12V Transformer |
| TL548 LED 60W 120 12AC BL | Black | 60W LED-Compatible Electronic Portable Plug-in 12V Transformer |

Specifications subject to change without notice.

APPLICATION

| Consideration | 12V Electronic Transformer | 12V Magnetic Transformer |
|------------------------|---|---|
| • Trac run length | • Use for short to medium run lengths and low to medium wattage systems | • Use for medium to long and medium to higher wattage systems |
| • Dimming | • Compatible with most standard incandescent dimmers. For optimal results use dimmer designed for low voltage electronics | • Use only dimmers specifically designed for use with magnetic transformers |
| • Transformer Location | • Install surface mount units in well-ventilated location where ambient temperature will not exceed 120°F (50°C) | • Install in well ventilated locations where ambient temperature will not exceed 140°F (60°C) Transformers must be accessible. |