



Ordering Information

| Catalog No. | Finishes | Mounting | Dimensions |
|-------------|-------------|---------------|--------------------|
| 7589 | Matte White | All Lytespan | 2 3/8" High |
| 7589 BK | Matte Black | Track Systems | 2" Wide 1" Deep |

Features

- Housing:** Molded polycarbonate .075" wall thickness; integral matte white finish.
- Movable Brass Contact:** Extends for connection to 2nd circuit in Advent Lytespan Track.
- Expansion Clamp:** Fingertip squeeze-release for quick attachment; thumbscrew lock for rigid mounting.
- Screw Terminals:** Connect onto individual conductors.
- Strain Relief Cap:** Molded thermoplastic. Use with pendant cord.
- Fixture Cord, Stem or Chain:** note: Cord max dia. .340" (not supplied). Stem size: 1/2" O.D., .065" wall, 1/4"-18 thread 1/2" long (not supplied). Chain: 1/4"-18 loop (not supplied).
- 1/4"-18 Knurled Ring.**
- 1/4"-20 Set Screw:** Nylon. Secures fixture cord, stem or chain loop.
- 1/4"-18 Nipple**
- Electrical Contacts:** move in conjunction with lever.
- Max. Wire Ga.:** #18
- Lever:** energizes attachment fitting.
- Polarity Keyway**

Electrical

Can be used with fixture cords up to a maximum diameter of 0.340"; suitable for 2 conductor and 3 conductor applications. Can also be used with stem or yoke supported fixtures terminating in 1/4" pipe size fittings.

Finish

All painted finishes baked enamel.

Labels

UL

Job Information

Type:

Job Name:

Cat. No.:

Lamp(s):

Notes:

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 www.lightolier.com © 2008 Philips Group • B0508