



Cylinder 261 UDX H: 18 W: 6 E: 11.25 MC: 9

Description

6" Square Up/Down cylinder wall-mount
Designed for use with LED light engines

Specifications

- Housing** Extruded aluminum cylinder with die-cast arm/back*
- Diffuser/Optics**
 - Bare lamp (open aperture)
 - Reflector
- Light Source** LED
- Max Watts** 14.31 X 2
- Electrical** COB/HO- L90 >55,000 Hr. TurboLED with 120-277V HPF Constant Current driver, LE-TE dimmable @120V or optional 0-10V dimming.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - For dry locations only



Ordering Guide: Choose from each category, using designated code to specify.

261 UDX					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

- Bare-lamp (open aperture)
- R** - Flood Reflector

Light Source

- 2TL6.2 HO** - 12.4W/40K 2972 Lm TurboLED
- 2TL6.5 COB** - 12.6W/30K 2270 Lm TurboLED
- 2TL7.8 HO** - 17.64W/40K 3528 Lm TurboLED
- 2TL9.4 HO** - 18.76W/40K 4078 Lm TurboLED
- 2TL9.5 COB** - 19.2W/30K 3364 Lm TurboLED
- 2TL11 HO** - 22.02W/40K 4620 Lm TurboLED
- 2TL11.5 COB** - 22.6W/30K 3894 Lm TurboLED
- 2TL12.7 HO** - 3.04W/40K 919 Lm TurboLED
- 2TL13 COB** - 26W/30K 4418 Lm TurboLED
- 2TL14.3 HO** - 28.62W/40K 5686 Lm TurboLED

2T61-2F13-QE

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 22K** Candlelight 90+ CRI (MOQ item - NCNR)
- 27K** Non-Stock item - consult factory for availability
- 2DIM010** LED 4-wire 0-10V Dimming - 120-277V
- 35K**
- 50K** Daylight (MOQ item - NCNR)
- SSP** 10KV 120-277V Supplemental Surge Protection

NOTES:
*Driver is housed in extended aluminum canopy (not shown)