Step 1 - Build Product

Step 2 - Add Accessories

Metalux

Wall Bracket LED

Product Page

Catalog Number

2BCLED-LD4-20SL-F-UNV-L840-CD1-U

Required Selections

Width

- (●) 2 = 2 Foot Width
- ( ) 4 = 4 Foot Width

Series

- (●) BCLED = LED Wall Bracket

Lamp Type

- (●) LD4 = LED 4.0

Lumen Output

- ( ) 8SL = 800 Lumens
- ( ) 28HL = 2800 Lumens
- ( ) 16SL = 1600 Lumens
- (●) 20SL = 2000 Lumens
- ( ) 24HL = 2400 Lumens
- ( ) 48HL = 4800 Lumens
- ( ) 32SL = 3200 Lumens
- ( ) 36SL = 3600 Lumens
- ( ) 40SL = 4000 Lumens
- ( ) 44HL = 4400 Lumens
- ( ) 28SL = 2800 Lumens

Shielding

- (●) F = Frost Acrylic (Standard)

Voltage

- (●) UNV = Universal Voltage 120/277
- ( ) 347V = 347 Volt
- ( ) 480V = 480 Volt
- ( ) 120V = 120 Volt
- ( ) 277V = 277 Volt
- ( ) XXX = Unknown Voltage
- ( ) UNC = Universal Voltage 347/480

Correlated Color Temp (CCT)

- ( ) L830 = 3000K
- ( ) L835 = 3500K
- (●) L840 = 4000K

Driver Type

- (●) CD = 0-10V Dimming (Standard)
- ( ) SD = Step-Dim
- ( ) 5LTD = Fifth Light DALI (10-100% Dimming)

Number of Drivers

- (●) 1 = 1 Driver

Packaging

- (●) U = Unit Pack