

# COOPER LIGHTING - METALUX®

## DESCRIPTION

The GR8 is a T8-dedicated lensed troffer designed to offer premium performance in a low profile housing. T8 dedication and optimized lamp to lens spacing provides the best in energy efficiency and optical control. The GR8's shallow, low profile housing is compatible with even highly restrictive plenums. Luminaires are compatible with today's popular ceiling systems.

The GR8 offers great performance and great quality. The series is an excellent choice for commercial offices, schools, hospitals, retail merchandising and many other applications.

Catalog #	2GR8332AUNVOSQHE3X 32T8UNVISNSCU	Type	
Project		Date	
Comments			
Prepared by			

## SPECIFICATION FEATURES

### Construction

Unitized low profile recessed housing is die formed of code gauge prime cold rolled steel with full length stiffeners and unibody endplate for added strength. Ballast cover is easily removed without tools. Die formed captive lampholder bracket fully encloses lampholder wiring for easy lampholder replacement. Ample KOs are provided for continuous row wiring. Built-in grid-lock feature for safety and convenience.

### Electrical\*\*

Ballasts are CBM/ETL Class "P" and are positively secured by mounting bolts. Rotor-lock lampholders. UL/CUL listed. Suitable for damp locations.

### Finish

Multistage, iron phosphate pretreatment ensures maximum bonding and rust inhibition. Lighting grade baked white enamel finish with premium reflectance for high efficiency.

### Hinging/Latching

Positive spring loaded steel latches and safety lock T-hinges provide secure, high quality door fit and allow hinging and latching from either side.

### Frame/Shielding

Heavy gauge flat steel door is die formed with reinforced mitered corners. Housing and door frame assemblies incorporate full width mechanical light traps. Light stabilized, acrylic prismatic lens.

### Controls


Fifth Light ballast options are offered for both 0-10V continuous dimming and DALI applications. Combine with energy-saving products like occupancy sensors, daylighting controls, and lighting relay panels from Cooper Controls ([www.coopercontrol.com](http://www.coopercontrol.com)) to maximize energy savings.




**2GR8**  
**32T8**  
**332**

2' X 4' TROFFER  
3 T8 LAMPS


General Purpose  
T8 Commercial Troffer



## MOUNTING DATA




## LAMP CONFIGURATIONS




## DOOR FRAMES

2GR8  
Flat, White  
Steel (White  
Latches)



## CEILING COMPATIBILITY



COOPER LIGHTING

## ENERGY DATA

Input Watts:  
EB Ballast & STD Lamps  
328T8 (67)  
332 (91)

Luminaire Efficacy Rating  
LER = FL-75  
Catalog Number: 2GR8-332A

Yearly Cost of 1000 lumens,  
3000 hrs at .08 KWH = \$3.20

\*Standard G (Grid) Type Fixtures can be field converted by adding trim kits. See Compatibility Section or Consult Factory.

\*\*Reference the lamp/ballast data in the Technical Section for specific lamp/ballast requirements.

\*\*\*When ordering Flange Kit for installation in drywall ceilings, see options and accessories compatibility section and ordering logic.

LAMPS CONTAIN MERCURY. DISPOSE ACCORDING TO LOCAL, STATE OR FEDERAL LAWS


**LINEAR DISCONNECT**

Safe and convenient means of disconnecting power.



ADF012708

PHOTOMETRICS



**2GR8-332A**  
 Electronic Ballast  
 (3) F28T8 lamps  
 3100 lumens  
 Spacing criterion:  
 (||) 1.2 x mounting  
 height, (L) 1.4 x  
 mounting height  
 Efficiency 77.6%  
 Test Report:  
 2GR8-332A.IES  
 LER = FL-75  
 Yearly Cost of 1000  
 lumens, 3000 hrs at  
 .08 KWH = \$3.20

Candela			
Angle	Along	45°	Across ⊥
0	2717	2717	2717
5	2719	2706	2716
10	2684	2685	2708
15	2622	2648	2691
20	2537	2592	2655
25	2419	2510	2594
30	2276	2400	2503
35	2101	2256	2383
40	1888	2059	2225
45	1630	1808	1991
50	1342	1537	1688
55	1082	1248	1345
60	847	928	1011
65	640	632	731
70	471	405	527
75	333	271	394
80	237	206	295
85	127	127	169
90	12	25	36

Coefficients of Utilization

rc	Effective floor cavity reflectance																	
	80%			70%			50%			30%			10%			0%		
rw	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	92	92	92	92	90	90	90	90	86	86	86	82	82	82	79	79	79	78
1	85	81	78	75	83	80	77	74	76	74	72	73	71	70	70	69	67	66
2	78	72	67	62	76	70	65	62	67	63	60	65	62	59	62	60	57	56
3	71	63	57	52	69	62	56	52	60	55	51	58	54	50	56	52	49	48
4	65	56	50	45	64	55	49	45	53	48	44	52	47	43	50	46	43	41
5	60	51	44	39	59	50	43	39	48	43	38	47	42	38	45	41	37	36
6	56	46	39	34	54	45	39	34	44	38	34	42	37	33	41	37	33	32
7	52	41	35	30	50	41	35	30	40	34	30	39	33	30	38	33	29	28
8	48	38	31	27	47	37	31	27	36	31	27	35	30	27	34	30	26	25
9	45	35	29	24	44	34	28	24	33	28	24	33	28	24	32	27	24	23
10	42	32	26	22	41	32	26	22	31	26	22	30	25	22	30	25	22	20

Zonal Lumen Summary

Zone	Lumens	%Lamp	%Fixture
0-30	2162	23.2	30.0
0-40	3564	38.3	49.4
0-60	6046	65.0	83.8
0-90	7213	77.6	100.0
0-180	7213	77.6	100.0

Luminance Data

Angle in Deg	Average 0-Deg cd/sm	Average 45-Deg cd/sm	Average 90-Deg cd/sm
45	3697	4101	4516
55	3026	3490	3761
65	2429	2399	2774
75	2064	1679	2442
85	2337	2337	3110

**ORDERING INFORMATION**

SAMPLE NUMBER: 2GR8-332A-UNV-EB81-U

<p><b>Rating<sup>(5)</sup></b> Blank= Standard ATW-SW4= Chicago Rated</p> <p><b>Width</b> 2=2' Width</p> <p><b>Trim Type</b> G=Grid/Lay-in (Standard)</p> <p><b>Series</b> R8=General Purpose T8 Commercial Troffer<sup>(1)</sup></p>	<p><b>Number of Lamps<sup>(4)</sup></b> 3=3 Lamps (Not included)</p> <p><b>Wattage</b> 28T8=28W T8 (48") 32=32W T8 (48")</p> <p><b>Shielding</b> A=#12 Acrylic Pattern A125=#12 Pattern Acrylic (.125" Thick) A19/156=#19 Pattern Acrylic (.156" Thick) PB1S=Silver Parabolic Louver (1/2" x 1/2" x 1/2")</p>	<p><b>Voltage<sup>(2)</sup></b> 120V=120 Volt 277V=277 Volt 347V=347 Volt UNV=Universal Voltage 120-277<sup>(3)</sup></p> <p><b>Options</b> GL=Single Element Fuse GM=Double Element Fuse Flex=Flex Installed EL=Emergency Installed</p>	<p><b>Ballast Type</b> BALLIST ADDED FOR ITEM OSQHE3X32T8UNVISNSC</p> <p>—</p> <p>— Total Harmonic Distortion &lt; 10%. Low Ballast Factor .77 - .82</p> <p><b>HB8_N</b>=T8 Electronic Instant Start. Total Harmonic Distortion &lt; 10%. Normal Ballast Factor 1.0</p> <p><b>HB8_H</b>=T8 Electronic Instant Start. Total Harmonic Distortion &lt; 10%. High Ballast Factor 1.15 - 1.20</p> <p><b>HR8_T8</b> Electronic Program Rapid Start. Total Harmonic Distortion &lt; 10%. Standard Ballast Factor .86 - .88</p> <p><b>HR8_DIM</b>=T8 Electronic Program Rapid Start. Total Harmonic Distortion &lt; 10%. Step Dimming. Ballast Factor .88</p> <p><b>HR8_L</b>=T8 Electronic Program Rapid Start. Total Harmonic Distortion &lt; 10%. Low Ballast Factor .71 - .79</p> <p><b>HR8_H</b>=T8 Electronic Program Rapid Start. Total Harmonic Distortion &lt; 10%. High Ballast Factor 1.15 - 1.20</p> <p><b>Fifth Light DALI Ballasts<sup>(6)</sup></b> <b>5LT8_</b>=T8 DALI Program Rapid Start. Total Harmonic Distortion &lt; 10%. Ballast Factor 1.0<sup>(7)</sup></p>	<p><b>Options</b> FR=Fire Label</p> <p><b>Packaging</b> U=Unit Pack</p> <p><b>ACCESSORIES</b> EQ-CLIP-U=T-BAR Safety Earthquake Clips<sup>(11)</sup> FCTKA-24W-U=Field Installed Flange Kit</p> <p><b>FCTK</b> <b>A - 24</b> <b>R W - U</b></p> <p>Trim Kit Field Convertible</p> <p>Aluminum</p> <p>22=2' x 2' 24=2' x 4'</p> <p>Blank=Single R=In Row E=End Row</p> <p>N=Natural W=White</p> <p>U=Unit Pack</p>
<p><b>Number of Ballasts</b> 1=1 Ballast 2=2 Ballasts 3=3 Ballasts</p>				

**NOTES:** <sup>(1)</sup> An EQ Grid Clip is recommended for all 9/16" ceiling systems. Four required per fixture. <sup>(2)</sup> Products also available in non-US voltages and frequencies for international markets. <sup>(3)</sup> Not available when specifying emergencies, voltage must be specific. <sup>(4)</sup> Standard off-center ballast compartment on 3-lamp fixtures. <sup>(5)</sup> For NYC rated product, see separate specification sheets. <sup>(6)</sup> For a complete listing of Fifthlight Technology products and other solutions from Cooper Controls, visit [www.coopercontrol.com](http://www.coopercontrol.com). <sup>(7)</sup> For 5LT8 Fifth Light DALI, 3-lamp models require (2) ballasts.

Specifications & dimensions subject to change without notice. Consult your Cooper Lighting Representative for availability and ordering information.

**SHIPPING INFORMATION**

Catalog No.	Wt.
2GR8-328T8A	20 lbs.
2GR8-332A	20 lbs.