Versatile incandescent cylinder for pendant, cord, ceiling or wall mounting. Simplicity of design makes this an ideal fixture for applications where PAR halogen lamps are desired.

## **PRODUCT DATA**

HOUSING: Spun 1100-0 aluminum, .060 thick standard with white powder coat finish. Optional color as specified. The cylinder can be supplied for surface, wall, suspended by swivel pendant, or cord mount (see below).

**ELECTRICAL:** Input 120 VAC, rated for 100 Watts maximum. ETL/CETL Damp Location Listed.

**SOCKET:** Medium Base Porcelain with nickel plated brass screw shell.

MOUNTING: (Specify when ordering.)

Ceiling (Surface) Mount - Provided with mounting holes for securement to 4" octagon junction box.


Wall Mount - Diecast aluminum bracket protrudes 3.25" from wall and mounts to 4" octagon junction box.

Cord Mount - 10' Straight cord.


**Pendant Mount** – Swivel mount canopy allows cylinder to hang plumb up to 30° sloped ceiling stem 3/8" IPS (specify length) canopy adds 1.5" to overall length. Standard finish white powder coat. Specify Pendant Kit as follows:

Manufactured and tested to UL#1598 and

Note: Suitable for damp location.



CSA standards.





## SERIES C8S

Incandescent PAR30/PAR38 6" x 9" Cylinder Downlight



Cylinder shown in cord mount style.


Wall mount style


Catalog #: C8S

For Damp Location

Example: C8SIP30BWC

## Lamp/Wattage **Fixture Series Surface** C8SI P30 PAR30 **Pendant** C8PI Wall P38 PAR38 C8WI (100 Watt Max.) **Cord Mount** C8CI





Fixture:	Type:
Project:	

All Pathway® products meet or exceed requirements as established by the National Electrical Code. Specifications subject to change without notice. Alzak® is a registered trademark of Alcoa.

For other finishes, consult Sales Representative.

