



T3



T3



BT4



BT4

## DOUBLE END QUARTZ LAMPS

A suitable protective shield, screening technique or both shall be used to protect people and surroundings from the possibility of a lamp shattering and from possible ultraviolet radiation.

Watts	Bulb	Base	Product Number	Symbols & Footnotes	Ordering Abbreviation	Volts	Pkg Qty	Lamp Finish	Class & Filament	Avg Rated Life(hrs)	Lumens CCT	LCL (in)	MOL (in)
300	T3	RSC	58920	123,139	<b>300T3Q/CL/RP(EHM)</b>	120	6	Clear	C,C-8	2000	6000 2950		4.69
			59000	123,139	<b>300T3Q/CL</b>	130	20	Clear	C,C-8	2000	6000 2950		4.69
500	T3	RSC	58996	123,139	<b>500T3Q/CL(FCL)</b>	120	20	Clear	C,C-8	2000	8750 2950		4.69
			58865	123,139	<b>500T3Q/CL/RP(FCL)</b>	120	6	Clear	C,C-8	2000	8750 2950		4.69
			58997	123,139	<b>500T3Q/CL</b>	130	20	Clear	C,C-8	2000	8750 2950		4.69
1000	T3	RSC	58948	123,139	<b>1000T3Q/CL</b>	240	12	Clear	C,C-8	2000	21500 2950		10.06
1500	T3	RSC	58859	123,139	<b>1500T3Q/CL</b>	208	12	Clear	C,C-8	2000	33000 2950		10.06
			58857	123,139	<b>1500T3Q/CL</b>	240	12	Clear	C,C-8	2000	33000 2950		10.06
			58858	123,139	<b>1500T3Q/CL</b>	277	12	Clear	C,C-8	2000	33000 2950		10.06

## OSRAM MINISTAR LAMPS

Suitable for use in unshielded fixtures. Consult most recent luminaire standards for your area to determine luminaire requirements.

Watts	Bulb	Base	Product Number	Symbols & Footnotes	Ordering Abbreviation	Volts	Pkg Qty	Beam Type	Class & Filament	Avg Rated Life(hrs)	Lumens CCT	CBCP	Beam Angle	MOL (in)
10	T3	G4 Bipin	58520	72,84,123,145	<b>10T3Q/MINISTAR/S</b>	12	40	FL	C,C-8	2000	3000	80	35 x 60	1.31
20	T3	G4 Bipin	58521	72,84,123,145	<b>20T3Q/MINISTAR/S</b>	12	40	FL	C,C-8	2000	3000	120	35 x 60	1.31
		BT4	GY6.35 Bipin	58518	72,84,123,145	<b>20BT4Q/MINISTAR/AX</b>	12	40	FL	C,C-8	2000	3000	800	20
35	BT4	GY6.35 Bipin	58519	72,84,123,145	<b>35BT4Q/MINISTAR/AX</b>	12	40	FL	C,C-8	2000	3000	1000	30	1.75

## BI-PIN IR LAMPS

UV Filter capsule with axial filament and infrared reflective coating. Suitable for use in unshielded fixtures. Consult most recent luminaire standards for your area to determine luminaire requirements.

Watts	Bulb	Base	Product Number	Symbols & Footnotes	Ordering Abbreviation	Volts	Pkg Qty	Lamp Finish	Class & Filament	Avg Rated Life(hrs)	Lumens CCT	LCL (in)	MOL (in)
25	BT4	GY6.35 Bipin	58897	145	<b>25BT4Q/IR</b>	12	40	Clear	C,AXIAL	4000	450 3000	1.13	1.75
35	BT4	GY6.35 Bipin	58896	145	<b>35BT4Q/IR</b>	12	40	Clear	C,AXIAL	4000	800 3000	1.13	1.75