


BULB IDENTIFICATION

Light Center Length (L.C.L.) is the distance from the center of the light source to the following point for the base used:
Screw bases...bottom base contact; Bayonet candelabra and medium bayonet...top of base pins.



Bulb size – Max. Diameter (Divide by 8)

A-21 – $21/8 = 2\ 5/8$ " Dia.

G-40 – $40/8 = 5$ " Dia.

T-12 – $12/8 = 1\ 1/2$ " Dia.

PS-30 – $30/8 = 3\ 3/4$ " Dia.

BASE IDENTIFICATION

Typical bases are shown. One lead-in wire is soldered to the center contact and the other soldered or welded to the upper rim of the base shell. Base shells are typically made of brass or aluminum. ANSI designations are in parentheses.



Candelabra cand. (E12)



Intermediate Inter. (E17)




Medium (E26) & Medium Brass (E26)




3 Contact Medium 3 C Med (E26D)



Double Contact Bayonet D.C. Bay (BA15D)



Mogul Screw




3 Contact Mogul



Medium Skirted Med. Skirt (E26/50x39)

FILAMENT IDENTIFICATION

A FILAMENT designation consists of a prefix letter to indicate whether the wire is straight or coiled, and a number to indicate the arrangement of the filament on the supports. Prefix letters include: C (coiled) – wire is wound into a helical coil or it may be deeply fluted; CC (coiled coil) – wire is wound into a helical coil and this coiled wire again wound into a helical coil.



C-8 CC-8



C-9 CC-9




C-6 CC-6



C-2V CC-2V




C-7A CC-7A



C-11V



C-11 CC-11



C-17





C-2R



C-7

ADDITIONAL INFORMATION

Lamps listed 115-125 volts (design voltage 120), 120-130 volts (design voltage 125), 125-130 volts (design voltage 130) and 230-250 volts (design voltage 240) are intended for use on circuits normally varying within these voltage limits.



Finishes

W or SW - Soft White
DAY - Daylight®
Y - Yellow
B - Blue
R - Red
G - Green
A - Amber
IC - Iridescent clear
FL - Flood
SP - Spot
IF - Inside frost
AIC - Amber iridescent clear

INCANDESCENT LAMP SHAPES

A bulb designation consists of a letter(s) to indicate the shape and a figure to indicate the approximate major diameter in eighths of an inch. For example, an F-15 bulb is a flame-shape, 15/8 of an inch or 1-7/8 inches in diameter.



HOW TO READ PRODUCT INFORMATION – INCANDESCENT

Nominal Wattage	MOL (in)	Base	Product Number	Ordering Abbreviation	Voltage	Pkg Qty	Finish	Avg Rated Life (hrs)	CCT CRI	Lumens	Filament	Legislation Impact	Notes
Bulb		Describes the shape of the envelope followed by the lamp's major diameter given in eighths of an inch. See page 39: Incandescent Lamps.											
Base		See page 38: Base Identification.											
Symbols & Footnotes		All symbols and footnotes that apply to a specific product will appear in this space. The explanations of the symbols and footnotes are at the end of the incandescent section.											
Ordering Abbreviation		A text description of the lamp. See below for several examples and explanations of some of the codes.											
Lumens, Beam Angle, CBCP		These columns may contain data for any of these values.											

HOW TO READ ORDERING ABBREVIATIONS

40B10C/CRYSTAL/DL/BL/2PK		60A/DL/SW/2PK/RP		65BR30/DL/FL/RP	
40	Nominal lamp wattage	60	Nominal lamp wattage	65	Nominal lamp wattage
B	Bulb shape	A	Bulb shape	BR	Bulb shape
10	Bulb size in 8th's of an inch	DL	Double Life lamp	30	Bulb size in 8th's of an inch
C	Candelabra base	SW	Soft white	DL	Double Life lamp
CRYSTAL	Crystal texture on bulb glass	2PK	2 lamps per package	FL	Flood beam pattern
DL	Double Life lamp	RP	Retail pack	RP	Retail pack
BL	Blister pack				
2PK	2 lamps per package				

For the current listing of available products and more complete product information, please visit us at www.sylvania.com.



DECORATIVE INCANDESCENT LAMPS

Incandescent C7 Night Lights

Nominal Wattage	MOL (in)	Base	Product Number	Ordering Abbreviation	Voltage	Pkg Qty	Finish	Average Rated Life (hrs)	CCT (K)	CRI	Lumens	Filament	Notes
4	2.13	Candelabra	13498	4C7/CR/BL/4PK 120V	120	48	Crystal	3000	2850	100	15	C-9	●●●
			13542	4C7/BL/2PK 120V	120	24	Clear	3000	2850	100	15	C-9	●●●
			13523	4C7/DL/BL/4PK 120V	120	48	Clear	6000	2850	100	14	C-9	●●●
			13549	4C7/BL/4PK 120V	120	48	Clear	3000	2850	100	15	C-9	●●●
			13553	4C7/W/BL/4PK 120V	120	48	White	3000	2850	100	15	C-7	●●●
7	2.13	Candelabra	13543	7C7/BL/2PK 120V	120	24	Clear	3000	2850	100	40	C-9	●●●
			13545	7C7/BL/4PK 120V	120	48	Clear	3000	2850	100	40	C-9	●●●
			13608	7C7 120V	120	120	Clear	3000	2850	100	40	C-9	●●●
			13609	7C7 130V	130	120	Clear	3000	2850	100	40	C-9	●●●
			13540	7C7/W/BL/2PK 120V	120	24	White	3000	2850	100	30	C-9	●●●
			13544	7C7/W/BL/4PK 120V	120	48	White	3000	2850	100	30	C-9	●●●
10	2.13	Candelabra	13636	10C7/CL 120V	120	240	Clear	3000	2850	100	35	C-7A	●●●

Incandescent B10 and B13 Lamps

Incandescent B10 Bent and Blunt Tip

Nominal Wattage	MOL (in)	Base	Product Number	Ordering Abbreviation	Voltage	Pkg Qty	Finish	Average Rated Life (hrs)	CCT (K)	CRI	Lumens	Filament	Notes
15	3.88	Candelabra	13657	15B10CBAGPK 120V	120	200	Clear	1500	2850	100	70	C-7A	▼●●
			13307	15B10C/DL/BL/4PK 120V	120	24	Clear	3000	2850	100	65	C-7A	▼●●
			13448	15B10C/BL/2PK 120V	120	12	Clear	1500	2850	100	65	C-7A	▼●●
15	3.63	Candelabra	13675	15B10C/T/BL/2PK 120V	120	12	Clear	1500	2850	100	70	C-7A	▼●●
15	3.88	Candelabra	13315	15B10C/DL/BL 120V	120	12	Clear	3000	2850	100	65	C-7A	▼●●
15	3.81	Medium	13433	15B10/BL/2PK 120V	120	12	Clear	1500	2850	100	70	C-7A	▼●●
15	3.56	Medium	13715	15B10/T/BL/2PK 120V	120	12	Clear	1500	2850	100	70	C-7A	▼●●
25	3.88	Candelabra	13306	25B10C/DL/BL/4PK 120V	120	24	Clear	3000	2850	100	150	C-7A	▼●●
			13316	25B10C/DL/BL 120V	120	12	Clear	3000	2850	100	150	C-7A	▼●●
			13452	25B10C/BL/2PK 120V	120	12	Clear	1500	2850	100	175	C-7A	▼●●
			13647	25B10C/BL/4PK 120V	120	24	Clear	1500	2850	100	175	C-7A	▼●●
			13452	25B10C/BL/2PK 120V	120	12	Clear	1500	2850	100	175	C-7A	▼●●
25	3.63	Candelabra	13678	25B10C/T/BL/2PK 120V	120	12	Clear	1500	2850	100	175	C-7A	▼●●
25	3.81	Medium	13318	25B10/DL/BL 120V	120	12	Clear	3000	2850	100	150	C-7A	▼●●
			13331	25B10/DL/BL/4PK 120V	120	24	Clear	3000	2850	100	150	C-7A	▼●●
			13438	25B10/BL/2PK 120V	120	12	Clear	1500	2850	100	175	C-7A	▼●●
			13654	25B10/BL/4PK 120V	120	24	Clear	1500	2850	100	175	C-7A	▼●●
25	3.56	Medium	13717	25B10/T/BL/2PK 120V	120	12	Clear	1500	2850	100	175	C-7A	▼●●
25	4.44	Candelabra	13748	25B10C/CRYSTAL/DL/BL/4/24 120V	120	24	Crystal	3000	2850	100	150	C-7A	▼●●
25	3.88	Candelabra	13308	25B10C/DLF/BL/4PK 120V	120	24	Frosted	3000	2850	100	145	C-7A	▼●●
			13317	25B10C/DLF/BL 120V	120	12	Frosted	3000	2850	100	145	C-7A	▼●●
			13453	25B10C/F/BL/2PK 120V	120	12	Frosted	1500	2850	100	145	C-7A	▼●●
25	3.81	Medium	13439	25B10/F/BL/2PK 120V	120	12	Frosted	1500	2850	100	165	C-7A	▼●●
25	4.44	Candelabra	13395	25B10C/F/BL/4PK 120V	120	24	Frosted	1500	2850	100	165	C-7A	▼●●

Specifications subject to change without notice.

Notes on page 53