

photo
not
available

Product Number: 55134

Order Abbreviation: 20MR11/T/FL35/C(FTD) 12V

General Description: Tungsten Halogen Tru-Aim MR11 UV-Stop Capsule With Axial Filament, Dichroic Reflector GU4 Bi-Pin Base 20Watt 12Volt Flood Beam (FTD)

Product Information

Abbrev. With Packaging Info.	20MR11TFL35CFTD 12V 10/CS 1/SKU
ANSI Code	FTD
Average Rated Life (hr)	4000
Base	G4 Bipin
Beam Angle (deg)	35
Beam Type	FL
Bulb	MR11
Centerbeam Candlepower (cp)	700
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature/CCT (K)	3000
Diameter (in)	1.375
Diameter (mm)	35.000
Ecologic	YES
Family Brand Name	TRU-AIM TITAN®
Filament	AXIAL
Horizontal Beam Angle (deg)	35
Maximum Overall Length - MOL (in)	1.500
Maximum Overall Length - MOL (mm)	37.000
Nominal Voltage (V)	12.00
Nominal Wattage (W)	20.00
Vertical Beam Angle (deg)	35

Additional Product Information

Product Documents, Graphs, and Images

Packaging Information



**Footnotes**

- Max. seal temperature 370 C (662F)
- UV Filter capsule with axial filament in covered constant color, hard coated dichroic reflector.
- Max pin temperature 250 C.
- Max temperature at lens reflector joint 240 C.

[Print Page](#)