

20MR16IRFL40C



Product Number: 58533

Order Abbreviation: 20MR16/IR/FL35/C 12V

General Description: Tungsten Halogen Tru-Aim MR16 IR UV-Filter Capsule Axial Filament Hard Dichroic Reflector GU5.3 Bi-Pin Base 20Watt 12Volt Flood Beam

*** Not for Sale/Purchase in California**

Product Information	
Abbrev. With Packaging Info.	20MR16IRFL35C 12V 20/CS 1/SKU
Approx. Lumens	380
Average Rated Life (hr)	5000
Base	GU5.3 Bipin
Beam Angle (deg)	36
Beam Type	WFL
Bulb	MR16
Centerbeam Candlepower (cp)	1000
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature/CCT (K)	3000
Diameter (in)	2.008
Diameter (mm)	51.00
Ecologic	YES
Family Brand Name	TRU-AIM® IR
Filament	AXIAL
Horizontal Beam Angle (deg)	40
Lamp Finish	Covered
Maximum Overall Length - MOL (in)	1.750
Maximum Overall Length - MOL (mm)	45
Nominal Voltage (V)	12.00
Nominal Wattage (W)	20.00
Vertical Beam Angle (deg)	40



Footnotes

- Infrared lamp technology
- Max. seal temperature 370 C (662F)

- UV Filter capsule with axial filament in covered constant color, hard coated dichroic reflector and infrared reflective coating on the lamp capsule.
- Max pin temperature 220 C.
- Max temperature at lens reflector joint 240 C.