

35MR1130FL



**Product Number:** 55136

**Order Abbreviation:** 35MR11/T/FL35/C(FTH) 12V

**General Description:** Tungsten Halogen Tru-Aim MR11 Titan Axial Filament UV-Filter Capsule Dichroic Reflector Cover Glass GU4 Bi-Pin Base 35Watt 12Volt Flood Beam (FTH)

**\* Full Case Required \* Not for Sale/Purchase in California**

| Product Information               |                                 |
|-----------------------------------|---------------------------------|
| Abbrev. With Packaging Info.      | 35MR11TFL35CFTH 12V 10/CS 1/SKU |
| ANSI Code                         | FTH                             |
| Approx. Lumens                    | 580                             |
| Average Rated Life (hr)           | 4000                            |
| Base                              | GU4 Bipin                       |
| Beam Angle (deg)                  | 36                              |
| Beam Type                         | WFL                             |
| Bulb                              | MR11                            |
| Centerbeam Candlepower (cp)       | 1350                            |
| Class                             | C (gas)                         |
| Color Rendering Index (CRI)       | 100                             |
| Color Temperature/CCT (K)         | 3000                            |
| Diameter (in)                     | 1.378                           |
| Diameter (mm)                     | 35.00                           |
| Ecologic                          | YES                             |
| Family Brand Name                 | TRU-AIM TITAN®                  |
| Filament                          | AXIAL                           |
| Horizontal Beam Angle (deg)       | 40                              |
| Lamp Finish                       | Covered                         |
| Maximum Overall Length - MOL (in) | 1.500                           |
| Maximum Overall Length - MOL (mm) | 37                              |
| Nominal Voltage (V)               | 12.00                           |
| Nominal Wattage (W)               | 35.00                           |
| Vertical Beam Angle (deg)         | 40                              |



**Footnotes**

- Max. seal temperature 370 C (662F)
- UV Filter capsule with axial filament in covered constant color, hard coated dichroic reflector.
- Max pin temperature 250 C.
- Max temperature at lens reflector joint 240 C.