

SPECIALTY HALOGEN LAMPS (cont.)
Double End Quartz 120V Halogen Lamps

Nominal Wattage	Bulb Shape	MOL (in)	Base	Product Number	Ordering Abbreviation	Finish	Pkg Qty	Average Rated Life (hrs)	Initial Lumens	CCT (K)	CRI	Filament	Notes
100	T3	3.13	R7s RSC	58999	100T3Q/S/CL 120V	Clear	20	2000	1600	2950	100	CC-8	6,7,12
				58887	100T3Q/S/CL/RP 120V	Clear	6	2000	1600	2950	100	CC-8	6,7,12
150	T3	3.13	R7s RSC	58885	150T3Q/CL/RP 120V	Clear	6	2000	2250	2950	100	CC-8	6,7,12
				58886	150T3Q/S/CL/RP 120V	Clear	6	2000	2400	2950	100	CC-8	6,7,12
				59001	150T3Q/S/CL 120V	Clear	20	2000	2400	2950	100	CC-8	6,7,12
200	T3	4.69	R7s RSC	59003	200T3Q/CL 120V	Clear	20	2000	3350	2950	100	CC-8	6,7,12
250	T3	4.69	R7s RSC	58527	250T3Q/CL/RP 120V	Clear	12	2000	4000	2950	100	CC-8	6,7,12
300	T3	4.69	R7s RSC	58920	300T3Q/CL/RP(EHM) 120V	Clear	6	2000	6000	2950	100	CC-8	6,7,12
				58998	300T3Q/CL(EHM) 120V	Clear	20	2000	6000	2950	100	CC-8	6,7,12
500	T3	4.69	R7s RSC	58865	500T3Q/CL/RP(FCL) 120V	Clear	6	2000	8750	2950	100	CC-8	6,7,12
				58996	500T3Q/CL(FCL) 120V	Clear	20	2000	8750	2950	100	CC-8	6,7,12

Double End Quartz 130V Halogen Lamps

Nominal Wattage	Bulb Shape	MOL (in)	Base	Product Number	Ordering Abbreviation	Finish	Pkg Qty	Average Rated Life (hrs)	Initial Lumens	CCT (K)	CRI	Filament	Notes
300	T3	4.69	R7s RSC	59000	300T3Q/CL 130V	Clear	20	2000	6000	2950	100	CC-8	6,7,12
500	T3	4.69	R7s RSC	58997	500T3Q/CL 130V	Clear	20	2000	8750	2950	100	CC-8	6,7,12

Single End BiPin Halogen Lamps with Axial Filament (12V)

Nominal Wattage	Bulb Shape	MOL (in)	Base	Product Number	Ordering Abbreviation	Finish	Pkg Qty	Average Rated Life (hrs)	Initial Lumens	CCT (K)	CRI	Filament	Notes
10	T3	1.25	G4 Bipin	58691	10T3Q/CL/AX 12V	Clear	40	4000	130	3000	100	Axial	6,7,12
20	T3	1.25	G4 Bipin	58694	20T3Q/CL/AX 12V	Clear	40	2000	320	3000	100	Axial	6,7,12
20	T4	1.75	GY6.35 Bipin	58663	20T4Q/CL/AX 12V	Clear	40	4000	290	3000	100	Axial	6,7,12
35	T4	1.75	GY6.35 Bipin	58672	35T4Q/CL/AX 12V	Clear	40	4000	580	3000	100	Axial	6,7,12
50	T4	1.75	GY6.35 Bipin	58676	50T4Q/CL/AX 12V	Clear	40	4000	900	3000	100	Axial	6,7,12
75	T4	1.75	GY6.35 Bipin	58680	75T4Q/CL/AX 12V	Clear	40	4000	1450	3000	100	Axial	6,7,12

Single End BiPin Halogen Lamps with Transverse Filament (12V)

Nominal Wattage	Bulb Shape	MOL (in)	Base	Product Number	Ordering Abbreviation	Finish	Pkg Qty	Average Rated Life (hrs)	Initial Lumens	CCT (K)	CRI	Filament	Notes
5	T3	1.25	G4 Bipin	58652	5T3Q/CL 12V	Clear	40	4000	60	3000	100	Transverse	6,7,12
10	T3	1.25	G4 Bipin	58650	10T3Q/CL/RP 12V	Clear	6	2000	140	3000	100	Transverse	6,7,12
				58658	10T3Q/CL 12V	Clear	40	2000	140	3000	100	Transverse	6,7,12
20	T3	1.25	G4 Bipin	58655	20T3Q/CL/RP 12V	Clear	6	2000	320	3000	100	Transverse	6,7,12
				58661	20T3Q/CL 12V	Clear	40	2000	320	3000	100	Transverse	6,7,12
50	T4	1.75	GY6.35 Bipin	58660	50T4Q/CL/RP 12V	Clear	6	2000	910	3000	100	Transverse	6,7,12
				58675	50T4Q/CL 12V	Clear	40	2000	910	3000	100	Transverse	6,7,12

Single End BiPin Lamps with Axial Filament (24V)

Nominal Wattage	Bulb Shape	MOL (in)	Base	Product Number	Ordering Abbreviation	Finish	Pkg Qty	Average Rated Life (hrs)	Initial Lumens	CCT (K)	CRI	Filament	Notes
20	T3	1.25	G4 Bipin	58662	20T3Q/CL/24V	Clear	40	1000	320	3000	100	Axial	6,7,12
50	T4	1.75	GY6.35 Bipin	58678	50T4Q/CL/AX/24V	Clear	40	2000	900	3000	100	Axial	6,7,12

¹ Life in Years based on 3 hours operation per day.
² Cost per Year based on 3 hours per day, \$0.11 per kWh.

For the current listing of available products and more complete product information, please visit us at www.sylvania.com.