



PAR20



PAR30LN



PAR38



PAR14



PAR16 GU10



PAR16

## CAPSYLITE® PAR DAYLIGHT PLUS™ PAR

## 60PAR16CAPNFL13

Watts	Bulb	Base	Product Number	Symbols & Footnotes	Ordering Abbreviation	Volts	Pkg Qty	Beam Type	Class & Filament	Avg Rated Life(hrs)	Lumens	CBCP	Beam Angle	MOL (in)
50	PAR20	E26 Med	15226	★     12	50PAR20/DAY/NFL/RP	120	6	Narrow Flood	C, CC-8	2000	460	1000	30	3 1/8
	PAR30LN	E26 Med	15227	★     12,15	50PAR30LN/DAY/WFL/RP	120	6	Wide Flood	C, CC-8	2000	580	550	50	4 5/8
	PAR38	E26 Med Skt	15229	★     12	50PAR38/DAY/FL/RP	120	6	Flood	C, CC-8	2000	560	1550	30	5 5/16
60	PAR38	E26 Med Skt	15252	★     12	60PAR38/CAP/DAY/SP9	120	15	Spot	C, CC-8	2500	725	13500	9	5 5/16
			15251	★     12	60PAR38/CAP/DAY/FL30	120	15	Flood	C, CC-8	2500	725	2150	30	5 5/16
75	PAR30LN	E26 Med	15228	★     12,15	75PAR30LN/DAY/WFL/RP	120	6	Wide Flood	C, CC-8	2000	1000	1000	50	4 5/8
	PAR38	E26 Med Skt	15230	★     12	75PAR38/DAY/FL/RP	120	6	Flood	C, CC-8	2000	960	2800	30	5 5/16

## CAPSYLITE® PAR14

Watts	Bulb	Base	Product Number	Symbols & Footnotes	Ordering Abbreviation	Volts	Pkg Qty	Beam Type	Class & Filament	Avg Rated Life(hrs)	Lumens	CBCP	Beam Angle	MOL (in)
35	PAR14	E26 Med	14553	12,16	35PAR14/CAP/FL50/RP	120	6	Flood	C, CC-8	2000	300	85	50	2 1/4

## DESIGNER 16® - CAPSYLITE® PAR16

Watts	Bulb	Base	Product Number	Symbols & Footnotes	Ordering Abbreviation	Volts	Pkg Qty	Beam Type	Class & Filament	Avg Rated Life(hrs)	Lumens	CBCP	Beam Angle	MOL (in)
50	PAR16	GU10	59020	★	50PAR16/HAL/GU10/FL/CLAM	120	6	Flood	C, CC-2V	1000	400	640	40	2 1/4
			59024	★	50PAR16/CAP/GU10/FL40	120	10	Flood	C, CC-2V	1000	400	640	40	2 1/4
60	PAR16	E26 Med	59037	12,16	60PAR16/HAL/NSP10/RP	120	6	Narrow Spot	C, CC-8	2000	650	5000	10	2 7/8
			59032	12,16	60PAR16/CAP/NSP10	120	15	Narrow Spot	C, CC-8	2000	650	5000	10	2 7/8
			59040	1,12,16	60PAR16/CAP/NSP10 <i>@ 120 volts, approximate 53 watts, 495 lumens, 4000 hours</i>	130	15	Narrow Spot	C, CC-8	2000	650	5000	10	2 7/8
			59031	12,16	60PAR16/HAL/NFL30/RP	120	6	Narrow Flood	C, CC-8	2000	650	1300	30	2 7/8
			59030	12,16	60PAR16/CAP/NFL30	120	15	Narrow Flood	C, CC-8	2000	650	1300	30	2 7/8
			59038	1,12,16	60PAR16/CAP/NFL30 <i>@ 120 volts, approximate 53 watts, 495 lumens, 4000 hours</i>	130	15	Narrow Flood	C, CC-8	2000	650	1300	30	2 7/8
75	PAR16	E26 Med	59035	12,16	75PAR16/HAL/NSP10/RP	120	6	Narrow Spot	C, CC-8	2000	900	7500	10	2 7/8
			59036	12,16	75PAR16/CAP/NSP10	120	15	Narrow Spot	C, CC-8	2000	900	7500	10	2 7/8
			59044	1,12,16	75PAR16/CAP/NSP10 <i>@ 120 volts, approximate 66 watts, 685 lumens, 4000 hours</i>	130	15	Narrow Spot	C, CC-8	2000	900	7500	10	2 7/8
			59033	12,16	75PAR16/HAL/NFL30/RP	120	6	Narrow Flood	C, CC-8	2000	900	1900	30	2 7/8
			59034	12,16	75PAR16/CAP/NFL30	120	15	Narrow Flood	C, CC-8	2000	900	1900	30	2 7/8
			59042	1,12,16	75PAR16/CAP/NFL30 <i>@ 120 volts, approximate 66 watts, 685 lumens, 4000 hours</i>	130	15	Narrow Flood	C, CC-8	2000	900	1900	30	2 7/8