


BULB IDENTIFICATION

Light Center Length (L.C.L.) is the distance from the center of the light source to the following point for the base used:
Screw bases...bottom base contact; Bayonet candelabra and medium bayonet...top of base pins.



Bulb size – Max. Diameter (Divide by 8)

A-21 – $21/8 = 2\ 5/8"$ Dia.

G-40 – $40/8 = 5"$ Dia.

T-12 – $12/8 = 1\ 1/2"$ Dia.

PS-30 – $30/8 = 3\ 3/4"$ Dia.

BASE IDENTIFICATION

Typical bases are shown. One lead-in wire is soldered to the center contact and the other soldered or welded to the upper rim of the base shell. Base shells are typically made of brass or aluminum. ANSI designations are in parentheses.



Candelabra cand. (E12)



Intermediate Inter. (E17)




Medium (E26) & Medium Brass (E26)




3 Contact Medium 3 C Med (E26D)



Double Contact Bayonet D.C. Bay (BA15D)



Mogul Screw



3 Contact Mogul



Medium Skirted Med. Skirt (E26/50x39)

FILAMENT IDENTIFICATION

A FILAMENT designation consists of a prefix letter to indicate whether the wire is straight or coiled, and a number to indicate the arrangement of the filament on the supports. Prefix letters include: C (coiled) – wire is wound into a helical coil or it may be deeply fluted; CC (coiled coil) – wire is wound into a helical coil and this coiled wire again wound into a helical coil.




C-8 CC-8



C-9 CC-9




C-6 CC-6



C-2V CC-2V




C-7A CC-7A



C-11V



C-11 CC-11



C-17





C-2R



C-7

ADDITIONAL INFORMATION

Lamps listed 115-125 volts (design voltage 120), 120-130 volts (design voltage 125), 125-130 volts (design voltage 130) and 230-250 volts (design voltage 240) are intended for use on circuits normally varying within these voltage limits.



Finishes

W or SW - Soft White
DAY - Daylight®
Y - Yellow
B - Blue
R - Red
G - Green
A - Amber
IC - Iridescent clear
FL - Flood
SP - Spot
IF - Inside frost
AIC - Amber iridescent clear

INCANDESCENT LAMP SHAPES

A bulb designation consists of a letter(s) to indicate the shape and a figure to indicate the approximate major diameter in eighths of an inch. For example, an F-15 bulb is a flame-shape, 15/8 of an inch or 1-7/8 inches in diameter.



HOW TO READ PRODUCT INFORMATION – INCANDESCENT

Nominal Wattage	MOL (in)	Base	Product Number	Ordering Abbreviation	Voltage	Pkg Qty	Finish	Avg Rated Life (hrs)	CCT CRI	Lumens	Filament	Legislation Impact	Notes
Bulb		Describes the shape of the envelope followed by the lamp's major diameter given in eighths of an inch. See page 39: Incandescent Lamps.											
Base		See page 38: Base Identification.											
Symbols & Footnotes		All symbols and footnotes that apply to a specific product will appear in this space. The explanations of the symbols and footnotes are at the end of the incandescent section.											
Ordering Abbreviation		A text description of the lamp. See below for several examples and explanations of some of the codes.											
Lumens, Beam Angle, CBCP		These columns may contain data for any of these values.											

HOW TO READ ORDERING ABBREVIATIONS

40B10C/CRYSTAL/DL/BL/2PK		60A/DL/SW/2PK/RP		65BR30/DL/FL/RP	
40	Nominal lamp wattage	60	Nominal lamp wattage	65	Nominal lamp wattage
B	Bulb shape	A	Bulb shape	BR	Bulb shape
10	Bulb size in 8th's of an inch	DL	Double Life lamp	30	Bulb size in 8th's of an inch
C	Candelabra base	SW	Soft white	DL	Double Life lamp
CRYSTAL	Crystal texture on bulb glass	2PK	2 lamps per package	FL	Flood beam pattern
DL	Double Life lamp	RP	Retail pack	RP	Retail pack
BL	Blister pack				
2PK	2 lamps per package				

For the current listing of available products and more complete product information, please visit us at www.sylvania.com.



A19 Med



A21 Med

SPECIALTY INCANDESCENT LAMPS (cont.)

Incandescent SAFELINE®, Rough Service and other Specialty Lamps

SAFELINE Incandescent A-Line Lamps

Nominal Wattage	MOL (in)	Base	Product Number	Ordering Abbreviation	Voltage	Pkg Qty	Finish	Average Rated Life (hrs)	CCT (K)	CRI	Lumens	Filament	Notes
75	5.31	Medium	12554	75A21/RS/SL/RP 120V	120	12	Safeline	1000	2850	100	800	C-9	●● ₁₀
100	5.31	Medium Brass	12834	100A21/SL 120V	120	48	Safeline	750	2850	100	1675	CC-8	● ₁₀
			12992	100A21/RS/SL/RP 120V	120	12	Safeline	1000	2850	100	1260	C-9	● ₁₀

Rough Service Incandescent A-Line Lamps

Nominal Wattage	MOL (in)	Base	Product Number	Ordering Abbreviation	Voltage	Pkg Qty	Finish	Average Rated Life (hrs)	CCT (K)	CRI	Lumens	Filament	Notes
50	4.44	Medium Brass	11068	50A19/RS 75V	75	120	Inside Frost	1000	2850	100	505	C-9	●
50	4.44	Medium	14070	50A/RS/2/RP 120V	120	24	Inside Frost	1000	2850	100	510	C-9	●●
60	4.44	Medium	12977	60A/RS/RP/1 120V	120	12	Inside Frost	1000	2850	100	555	C-9	●●
			13000	60A/RS/2/RP 120V	120	24	Inside Frost	1000	2850	100	555	C-9	●●
60	4.44	Medium Brass	13021	60A/RS/XL 120V	120	24	Inside Frost	5000	2850	100	450	C-9	●
60	4.44	Medium	12420	60A/RS/2/RP 130V	130	24	Inside Frost	1000	2850	100	555	C-9	●●
60	4.44	Medium Brass	12455	60A/RS/XL 130V	130	24	Inside Frost	5000	2850	100	450	C-9	●
60	4.44	Medium	10503	60A/RS/SL/RP 120V	120	12	Safeline	1000	2850	100	555	C-9	●● ₁₀
75	4.44	Medium	12579	75A/RS/RP/1 120V	120	12	Inside Frost	1000	2850	100	815	C-9	●●
			13001	75A/RS/2/RP 120V	120	24	Inside Frost	1000	2850	100	815	C-9	●●
75	4.44	Medium Brass	13022	75A/RS/XL 120V	120	24	Inside Frost	5000	2850	100	650	C-9	●
			12528	75A/RS/XL 130V	130	24	Inside Frost	5000	2850	100	700	C-9	●
75	4.44	Medium	12586	75A/RS/RP/1 130V	130	24	Inside Frost	1000	2850	100	815	C-9	●●
100	4.44	Medium	12998	100A/RS/2/RP 130V	130	24	Inside Frost	1000	2850	100	1260	C-9	●●
			12997	100A/RS/RP/1 120V	120	12	Inside Frost	1000	2850	100	1260	C-9	●●
			13002	100A/RS/2/RP 120V	120	24	Inside Frost	1000	2850	100	1260	C-9	●●
100	4.44	Medium Brass	13023	100A/RS/XL 120V	120	24	Inside Frost	5000	2850	100	840	C-9	●
			12559	100A/RS/XL 130V	130	24	Inside Frost	5000	2850	100	1040	C-9	●
150	6.06	Medium	15243	150A23/RS 130V	130	48	Inside Frost	1000	2850	100	2090	C-17	●●
200	5.88	Medium	15458	200A23/RS 130V	130	48	Inside Frost	1000	2850	100	2920	C-17	●●
200	6.06	Medium	15505	200A23 120V	120	48	Inside Frost	750	2850	100	3930	CC-8	●●

Other Specialty Incandescent A-Line Lamps

Nominal Wattage	MOL (in)	Base	Product Number	Ordering Abbreviation	Voltage	Pkg Qty	Finish	Average Rated Life (hrs)	CCT (K)	CRI	Lumens	Filament	Notes
25	3.94	Medium Brass	11714	25A19/TG/RP 125V	125	6	Green	3000	2850	100	180	C-9	●
			11710	25A19/TB/RP 125V	125	6	Blue	3000	2850	100	180	C-9	●
			11712	25A19/TR/RP 125V	125	6	Red	3000	2850	100	180	C-9	●
			11713	25A19/TY/RP 125V	125	6	Yellow – Buglight	3000	2850	100	180	C-9	●
60	4.44	Medium	10390	60A/Y/RP 120V	120	24	Yellow – Buglight	1000	–	–	–	CC-8	●●
			10386	60A/Y/RP 130V	130	24	Yellow – Buglight	1000	–	–	–	CC-8	●●
100	4.44	Medium	12763	100A/Y/RP 120V	120	24	Yellow – Buglight	1000	–	–	1140	CC-8	●●
60	4.44	Medium	10094	60A19/OBLUE 120V	120	12	Blue	1000	2850	100	705	C-9	●●
			12280	60A/GRO 120V	120	6	Spotgro	1000	–	–	705	C-9	●●
			11715	60A/BLACKLIGHT/RP 120V	120	6	Blacklight	1000	–	–	–	CC-8	2

For the current listing of available products and more complete product information, please visit us at www.sylvania.com.