



T8 IPS

SubstiTUBE® LED T8 Lamps

SubstiTUBE IPS LED T8 (Ballast Compatible, Glass, Dimmable)

Nominal Wattage ¹	Bulb Shape	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Rated Life L ₇₀ (hrs)	Beam Angle	Initial Lumens ¹	LPW	CCT (K)	CRI	Notes
15.5	T8	48	G13	75286	LED15T8/L48/DIM/830/SUB/G6	10	50,000	220°	2100	135	3000	82	4,11,12,13,14,16
				75287	LED15T8/L48/DIM/835/SUB/G6	10	50,000	220°	2100	135	3500	82	4,11,12,13,14,16
				75288	LED15T8/L48/DIM/841/SUB/G6	10	50,000	220°	2200	142	4100	82	4,11,12,13,14,16
				75297	LED15T8/L48/DIM/850/SUB/G6	10	50,000	220°	2200	142	5000	82	4,11,12,13,14,16

SubstiTUBE IPS LED T8 (Ballast Compatible, Glass)

Nominal Wattage ¹	Bulb Shape	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Rated Life L ₇₀ (hrs)	Beam Angle	Initial Lumens ¹	LPW	CCT (K)	CRI	Notes
12.0	T8	48	G13	79526	LED12T8/L48/FG/830/SUB/G6	10	50,000	220°	1650	138	3000	82	11,12,13,14,16
				79527	LED12T8/L48/FG/835/SUB/G6	10	50,000	220°	1650	138	3500	82	11,12,13,14,16
				79528	LED12T8/L48/FG/841/SUB/G6	10	50,000	220°	1650	138	4100	82	11,12,13,14,16
				79529	LED12T8/L48/FG/850/SUB/G6	10	50,000	220°	1650	138	5000	82	11,12,13,14,16
12.5	T8	36	G13	75128	LED12T8/L36/FG/830/SUB/G6	10	50,000	220°	1650	132	3000	82	11,12,13,14,16
				75129	LED12T8/L36/FG/835/SUB/G6	10	50,000	220°	1650	132	3500	82	11,12,13,14,16
				75130	LED12T8/L36/FG/841/SUB/G6	10	50,000	220°	1650	132	4100	82	11,12,13,14,16
				75131	LED12T8/L36/FG/850/SUB/G6	10	50,000	220°	1650	132	5000	82	11,12,13,14,16
8.5	T8	24	G13	75064	LED8T8/L24/FG/830/SUB/G6	10	50,000	220°	1100	129	3000	82	11,12,13,14,16
				75065	LED8T8/L24/FG/835/SUB/G6	10	50,000	220°	1100	129	3500	82	11,12,13,14,16
				75066	LED8T8/L24/FG/841/SUB/G6	10	50,000	220°	1100	129	4100	82	11,12,13,14,16
				75070	LED8T8/L24/FG/850/SUB/G6	10	50,000	220°	1100	129	5000	82	11,12,13,14,16

SubstiTUBE IPS LED T8 (Ballast Compatible, Plastic)

Nominal Wattage ¹	Bulb Shape	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Rated Life L ₇₀ (hrs)	Beam Angle	Initial Lumens ¹	LPW	CCT (K)	CRI	Notes
15.5	T8	48	G13	75132	LED15T8/L48/FP/830/SUB/G6	10	50,000	150°	2100	135	3000	82	11,12,13,14,16
				75133	LED15T8/L48/FP/835/SUB/G6	10	50,000	150°	2100	135	3500	82	11,12,13,14,16
				75134	LED15T8/L48/FP/841/SUB/G6	10	50,000	150°	2200	142	4100	82	11,12,13,14,16
				75135	LED15T8/L48/FP/850/SUB/G6	10	50,000	150°	2200	142	5000	82	11,12,13,14,16
12.5	T8	48	G13	75084	LED12T8/L48/F/830/SUB/G5	10	50,000	150°	1600	128	3000	82	11,12,13,14,16
				75085	LED12T8/L48/F/835/SUB/G5	10	50,000	150°	1600	128	3500	82	11,12,13,14,16
				75086	LED12T8/L48/F/841/SUB/G5	10	50,000	150°	1600	128	4100	82	11,12,13,14,16
				75087	LED12T8/L48/F/850/SUB/G5	10	50,000	150°	1600	128	5000	82	11,12,13,14,16

1. Lamp Power and Lamp Lumens rated on QHE2x32T8/UNV ISN.