

Product Number: 49863

Order Abbreviation: QHE 2X32T8/UNV ISL-SC

General Description: 2-lamp 32wT8 High Efficiency Instant Start electronic ballast, universal voltage, low ballast factor,10-pk



Product Information

| | |
|-----------------------------------|-------------------------------|
| Abbrev. With Packaging Info. | QHE2X32T8UNVISLSC 10/CS 1/SKU |
| Ballast Factor | 0.78 |
| Ballast Height H (in) | 1.1810 |
| Ballast Length L (in) | 9.4690 |
| Ballast Width W (in) | 1.6810 |
| Circuit Type | PARALLEL |
| Family Brand Name | QUICKTRONIC High-Efficiency |
| Input Current (Amps) | 0.00 |
| Nominal Voltage (V) | 120-277V |
| Number of Lamps | 2 |
| Open Circuit Voltage (V) | <600V |
| Power Factor | >0.97 |
| Primary Lamp Type | FO32/XP |
| Sound Rating | A |
| Starting Method | INSTANT START |
| Starting Temperature - Fahrenheit | -20 |
| Starting Temperature - Celsius | -29 |
| Total Harmonic Distortion (THD) | <10% |
| Wiring Method | Leads |
| Max Case Temperature | 10° c |



Footnotes

- Data based on primary lamp types. See OSRAM SYLVANIA System Performance Guide for data on other lamp combinations.
- Remote Mounting up to 18 feet
- 70C Max Case Temperature
- Complies with FCC 47 CFR Part 18, Non-Consumer
- Input Frequency: 50/60Hz.
- Minimum starting temperature: -20 F / -29 C