

QHE2X40UNVDLISNSC

Product Number: 49429

Order Abbreviation: QHE 2X40DL/UNV ISN-SC

General Description: QHE 2X40DL/UNV ISN SC



Product Information	
Abbrev. With Packaging Info.	QHE2X40DLUNVISNSC 10/CS 1/SKU
Ballast Factor	1.07
Ballast Height H (in)	1.1810
Ballast Length L (in)	9.4690
Ballast Width W (in)	1.6300
Circuit Type	PARALLEL
Family Brand Name	QUICKTRONIC
Input Current (Amps)	0.00
Nominal Voltage (V)	120-277V
Number of Lamps	2
Power Factor	>0.98
Primary Lamp Type	FT40DI/28WSS/IS
Sound Rating	A
Starting Method	INSTANT START
Starting Temperature - Fahrenheit	0
Starting Temperature - Celsius	-18
Total Harmonic Distortion (THD)	<10%
Wiring Method	LEADS

Footnotes
<ul style="list-style-type: none"> • Data based on primary lamp types. See LEDVANCE System Performance Guide for data on other lamp combinations. • Remote Mounting up to 18 feet • 70C Max Case Temperature • UL Listed Class P, Type 1 Outdoor • Insulate unused leads • Ground ballast case • Lampholder must be shorted per diagram • Install in accordance with National Electric Codes • Complies with FCC 47 CFR Part 18, Non-Consumer • ANSI 62.41 Cat. A Transient Protection • Class A Sound Rating. • Minimum Starting Temperature: 0F/-18C. • Input Frequency: 60Hz.