



**Product Number:** 49859

**Order Abbreviation:** QHE 2X59T8/UNV ISN-SC

**General Description:** 2-lamp 59wT8 (8') High Efficiency Instant Start electronic ballast, universal voltage, normal ballast factor, 10-pk.

Product Information	
Abbrev. With Packaging Info.	QHE2X59T8UNVISNSC 10/CS 1/SKU
Ballast Height H (in)	1.1810
Ballast Length L (in)	9.4690
Ballast Width W (in)	1.6810
Family Brand Name	QUICKTRONIC High-Efficiency
Input Current (Amps)	0.00
Nominal Voltage (V)	120-277V



**QUICK 60+**  
EFFICIENT WARRANTY

#### Footnotes

- Data based on primary lamp types. See LEDVANCE System Performance Guide for data on other lamp combinations.
- 70C Max Case Temperature
- UL Listed Class P, Type 1 Outdoor
- Ground ballast case
- Install in accordance with National Electric Codes
- ANSI 62.41 Cat. A Transient Protection
- Class A Sound Rating.
- Minimum Starting Temperature: 0F/-18C.
- Input Frequency: 50/60Hz.
- High power factor
- Minimum starting temperature: 60 F / 16 C with SS lamps
- Cutout Lampholder
- For any 2, 3 or 4 T12/RS/HO 800mA lamp combination provided total lamp length of each circuit (A) and circuit (B) is not less than 10 ft. nor more than 20 ft. Circuit "A" consists of lamp 1, 2 Circuit "B" consists of lamp 3, 4
- CSA certified.
- ANSI C82.11 where applicable.