

## QHE3X40UNVDLISNSC

**Product Number:** 49430

**Order Abbreviation:** QHE 3X40DL/UNV ISN-SC

**General Description:** QHE 3X40/DL UNV ISN SC



Product Information	
Abbrev. With Packaging Info.	QHE3X40DLUNVISNSC 10/CS 1/SKU
Ballast Factor	1.07
Ballast Height H (in)	1.1810
Ballast Length L (in)	9.4690
Ballast Width W (in)	1.6300
Circuit Type	PARALLEL
Family Brand Name	QUICKTRONIC
Input Current (Amps)	0.00
Nominal Voltage (V)	120-277V
Number of Lamps	3
Power Factor	>0.98
Primary Lamp Type	FT40DI/28WSS/IS
Sound Rating	A
Starting Method	INSTANT START
Starting Temperature - Fahrenheit	0
Starting Temperature - Celsius	-18
Total Harmonic Distortion (THD)	<10%
Wiring Method	LEADS

Footnotes
<ul style="list-style-type: none"> <li>• Data based on primary lamp types. See LEDVANCE System Performance Guide for data on other lamp combinations.</li> <li>• Remote Mounting up to 18 feet</li> <li>• 70C Max Case Temperature</li> <li>• UL Listed Class P, Type 1 Outdoor</li> <li>• Insulate unused leads</li> <li>• Ground ballast case</li> <li>• Lampholder must be shorted per diagram</li> <li>• Install in accordance with National Electric Codes</li> <li>• Complies with FCC 47 CFR Part 18, Non-Consumer</li> <li>• ANSI 62.41 Cat. A Transient Protection</li> <li>• Class A Sound Rating.</li> <li>• Minimum Starting Temperature: 0F/-18C.</li> <li>• Input Frequency: 60Hz.</li> </ul>