

Product Number: 51390

Order Abbreviation: QTP IX40TI5/UNV DALI

General Description: 1 lamp Universal Voltage 10 percent THD 100 to 3 percent electronic DALI digital dimming ballast for 40W T15 lamp



Product Information

Abbrev. With Packaging Info.	QTPIX40TI5UNVDALI 25/CS 1/SKU
Ballast Factor	1
Ballast Height H (in)	1.0000
Ballast Length L (in)	18.0500
Ballast Width W (in)	1.1800
Circuit Type	SERIES
Family Brand Name	QUICKTRONIC Professional
Input Current (Amps)	0.00
Nominal Voltage (V)	120-277V
Number of Lamps	1
Open Circuit Voltage (V)	<600
Power Factor	>0.95
Primary Lamp Type	FT40DL
Sound Rating	A
Starting Method	PROGRAMMED RAPID-START
Starting Temperature - Fahrenheit	50
Starting Temperature - Celsius	10
Total Harmonic Distortion (THD)	<10%
Wiring Method	WIRETRAPCONNECTORS

Footnotes

- Data based on primary lamp types. See OSRAM SYLVANIA System Performance Guide for data on other lamp combinations.
- 70C Max Case Temperature
- 75C Max Case Temperature
- Install in accordance with National Electric Codes
- Complies with FCC 47 CFR Part 18, Non-Consumer
- ANSI 62.41 Cat. A Transient Protection
- Class A Sound Rating.
- Input Frequency: 50/60Hz.
- Minimum Starting Temperature: 50F/IOC.
- High power factor