

Product 49120 Number:

Order **QTP 1X54T5HO/UNV PSN** Abbreviation:

General1- Lamp universal voltage electronic ballast for 54W T5 HO lamp. Packaged 10Description:pieces per case with wires

1100	fuct information
Abbrev. With Packaging Info.	QTP1X54T5HOUNVPSN 10/CS 1/SKU
Ballast Factor	1.00
Ballast Height H (in)	0.8660
Ballast Length L (in)	14.1340
Ballast Width W (in)	1.1810
Family Brand Name	QUICKTRONIC Professional
Input Current (Amps)	0.50
Nominal Voltage (V)	120-277V
Number of Lamps	1
Open Circuit Voltage (V)	<600
Power Factor	>0.98
Primary Lamp Type	FP54T5HO
Sound Rating	Α
Starting Method	PROSTART
Starting Temperature - Fahrenheit	0
Starting Temperature - Celsius	-18
Total Harmonic Distortion (THD)	<10%
Wiring Method	WIRETRAP CONNECTORS

**Product Information** 



## Footnotes

- Data based on primary lamp types. See LEDVANCE System Performance Guide for data on other lamp combinations.
- Product is a kit containing the core & coil, capacitor, ingitor (where required), brackets and mounting hardware
- Remote Mounting up to 18 feet
- Remote Mounting up to 12 feet
- Remote Mounting up to 10 feet
- Remote mounting defined by harness length
- Complies with FCC 47 CFR Part 18, Non-Consumer
- Remote Mounting up to 19 feet (keep red wires short for 1&2 lamp).
- Wiring diagram applies to instant start standard, low power (LP), PLUS, and HD10 ballast types.
- Oil Filled Capacitor
- Product contains installation instructions