

QTP2X263242CFUNVM



Product Number: 51843

Order Abbreviation: QTP2X26/32/42CF/UNV DM

General Description: Universal voltage programmed rapid start normal ballast factor electronic ballast in metal enclosure dual mount without leads for two 26W, 32W, or 42W CFL lamps.

Product Information	
Abbrev. With Packaging Info.	QTP2X263242CFUNVDM 20/CS 1/SKU
Ballast Factor	1
Ballast Height H (in)	1.3500
Ballast Length L (in)	4.9500
Ballast Width W (in)	2.9300
Circuit Type	SERIES
Family Brand Name	QUICKTRONIC Professional
Input Current (Amps)	0.00
Nominal Voltage (V)	120-277V
Number of Lamps	2
Power Factor	>0.98
Primary Lamp Type	26W DD/E,T/E
Sound Rating	A
Starting Method	PROGRAMMED RAPID START
Starting Temperature - Fahrenheit	-5
Starting Temperature - Celsius	-20
Total Harmonic Distortion (THD)	<10%
Wiring Method	PLUG-IN CONNECTORS
Language Strategy	2

Footnotes
<ul style="list-style-type: none"> • 70C Max Case Temperature • 75C Max Case Temperature • UL Listed Class P, Type 1 Outdoor • Ground ballast case • Install in accordance with National Electric Codes • Complies with FCC 47 CFR Part 18, Non-Consumer • Class A Sound Rating. • Input Frequency: 50/60Hz. • Remote Mounting up to 19 feet (keep red wires short for 1&2 lamp). • Minimum Starting Temperature: -4F/-20C. • Remote Mounting up to 19 feet (keep red wires short for 1&2 lamp models). • ANSI C62.41 cat. B3 Transient Protection. • Remote mounting - Typically 6ft with suitable ground plane, but varies by model and application. Contact ECS Application Engineering for information on longer applications.