

QTP2X26CFUNVBS

Product Number: 51833

Order Abbreviation: QTP 2X26/CF/UNV DM

General Description: LOW POWER DUAL ENTRY BALLAST.



Product Information	
Abbrev. With Packaging Info.	QTP2X26CFUNVDM 20/CS 1/SKU
Ballast Factor	1
Ballast Height H (in)	1.0630
Ballast Length L (in)	4.9450
Ballast Width W (in)	2.4020
Circuit Type	SERIES
Input Current (Amps)	0.00
Nominal Voltage (V)	120-277V
Number of Lamps	2
Power Factor	>0.98
Primary Lamp Type	26W DD/E,T/E
Sound Rating	A
Starting Method	PROGRAMMED RAPID START
Starting Temperature - Fahrenheit	-5
Starting Temperature - Celsius	-20
Total Harmonic Distortion (THD)	<10%
Wiring Method	PLUG-IN CONNECTORS
Language Strategy	1

Footnotes
• Remote Mounting up to 15 feet for one lamp and up to 6 feet for two lamps • 70C Max Case Temperature • 75C Max Case Temperature • UL Listed Class P, Type 1 Outdoor • Ground ballast case • Install in accordance with National Electric Codes • Complies with FCC 47 CFR Part 18, Non-Consumer • Class A Sound Rating. • Input Frequency: 50/60Hz. • Minimum Starting Temperature: -4F/-20C. • ANSI C62.41 cat. B3 Transient Protection.