

Product Number:

49843

Order Abbreviation:

QTP 2x32T8/UNV ISH-SC

General Description:

QTP2x32T8UNVISHSC 2-lamp 32wT8 Instant Start electronic ballast, universal voltage, high ballast factor, 10-pk



Product Information	
Abbrev. With Packaging Info.	QTP2X32T8UNVISHSC 10/CS 1/SKU
Ballast Factor	1.2
Ballast Height H (in)	1.1810
Ballast Length L (in)	9.4690
Ballast Width W (in)	1.6810
Circuit Type	PARALLEL
Family Brand Name	QUICKTRONIC Professional
Input Current (Amps)	0.00
Nominal Voltage (V)	120-277V
Number of Lamps	2
Open Circuit Voltage (V)	<600V
Power Factor	>0.98
Primary Lamp Type	FO32/XP
Sound Rating	A
Starting Method	INSTANT START
Starting Temperature - Fahrenheit	-20
Starting Temperature - Celsius	-29
Total Harmonic Distortion (THD)	<10%
Wiring Method	LEADS
Max Case Temperature	70°C

Footnotes
• Data based on primary lamp types. See LEDVANCE System Performance Guide for data on other lamp combinations. • Remote Mounting up to 18 feet • 70C Max Case Temperature • UL Listed Class P, Type 1 Outdoor • Ground ballast case • Lampholder must be shorted per diagram • Install in accordance with National Electric Codes • Complies with FCC 47 CFR Part 18, Non-Consumer • ANSI 62.41 Cat. A Transient Protection • Class A Sound Rating. • Input Frequency: 50/60Hz. • Minimum starting temperature: 60 F / 16 C with SS lamps • Minimum starting temperature: -20 F / -29 C