

QTP2X40TT5120



Product Number: 50340

Order Abbreviation: QTP 2X40TT5/120 PSN F

General Description: 2 lamp 120V 10 percent THD programmed rapid start normal ballast factor electronic ballast in an F enclosure size for FT40TT5 lamp

Product Information	
Abbrev. With Packaging Info.	QTP2X40TT5120PSNF 20/CS 1/SKU
Ballast Factor	0.88
Ballast Height H (in)	1.0000
Ballast Length L (in)	9.5000
Ballast Width W (in)	1.6000
Circuit Type	Series
Family Brand Name	QUICKTRONIC Professional
Input Current (Amps)	0.00
Nominal Voltage (V)	120V
Number of Lamps	2
Power Factor	>0.97
Primary Lamp Type	FT40DL
Sound Rating	A
Starting Method	Programmed Start
Starting Temperature - Fahrenheit	0
Starting Temperature - Celsius	-18
Total Harmonic Distortion (THD)	<10%
Wiring Method	Leads



Footnotes
<ul style="list-style-type: none"> • Data based on primary lamp types. See LEDVANCE System Performance Guide for data on other lamp combinations. • Remote Mounting up to 10 feet • 70C Max Case Temperature • UL Listed Class P, Type 1 Outdoor • Ground ballast case • Install in accordance with National Electric Codes • Complies with FCC 47 CFR Part 18, Non-Consumer • ANSI 62.41 Cat. A Transient Protection • Class A Sound Rating. • Minimum Starting Temperature: 0F/-18C. • Input Frequency: 60Hz.

