

DESCRIPTION

Rectilinear shaped light bar with multi-layered white glass or white acrylic. Plated pressure formed frame. Provides task and ambient light. May be mounted vertically or horizontally. Available in three lamp configurations: 24 watt high output T5 linear fluorescent lamp (lamp and electronic ballast included); four 120 volt, 40 watt halogen mini-candelabra base lamps, or energy saving 20 watt, 900 lumen, 3000K LED module. Incandescent version dimmable with standard incandescent dimmer. LED version dimmable with low-voltage electronic dimmer. ADA compliant.

INSTALLATION

This product can mount to either a 4" square electrical box with round plaster ring or an octagonal electrical box. For wall mount use only. 12.5" of clearance is needed on one side of the fixture to remove glass when relamping.


DIMMING

Incandescent version dimmable with a standard incandescent dimmer (not included).

WEIGHT

5.5lb / 2.49kg

ORDERING INFORMATION



700BCMET	COLOR	FINISH	LAMP
Y	ACRYLIC LENS	Z ANTIQUE BRONZE	INCANDESCENT 120V
	FROST	C CHROME	-CF FLUORESCENT 120V
		S SATIN NICKEL	-CF277 FLUORESCENT 277V
			-LED LED 3000K 120V

Acrylic not available with incandescent lamp.



7400 Linder Avenue T 847.410.4400
 Skokie, Illinois 60077 F 847.410.4500

www.techlighting.com

700BCMET _____

FIXTURE TYPE: _____

JOB NAME: _____

NOTES: _____

