



4123RP; 4124RP

APPLICATION and PERFORMANCE SPECIFICATION

Description: Magnetic ballast for (1) CFQ26W/G24d-3 Compact Fluorescent Lamp
or CFS28W/GR8 2D Lamp.

• Line Voltage: 120vac +/-10%, 60Hz

• Pre-Heat

Model	Line Volts	Input Watts	Nominal Line Amps	Starting Current(Amps)	Power Factor	Ballast Factor	Ballast Efficacy Factor	Power Factor	Harmonic Total	Crest Factor
4123RP*	120	33	0.68	0.88	> .50	.88	2.67	NPF	< 20%	<1.7
4124RP*	120	30	0.27	0.46	> .90	.88	2.93	HPF	< 20%	<1.7

* BE and BES versions have the same performance data

Performance:

- Meets ANSI Standard C82.11-1993
- Class P Thermally Protected

Safety:

- No PCB's
- UL listed (Class P, Type 1 Outdoor)
- CSA Certified

Application:

- Minimum Starting Temperature: 15 °F, -9 °C
- Maximum Case Temperature: 90 °C
- Sound Rated: A
- Leads: Side Exit
BE - Bottom Exit
BES - Bottom Exit w/Studs (Studs 2" O.C.)
- Other Models: **4123RPBE; 4123RPBES**
4124RPBE; 4124RPBES

Physical Parameters:

	4123RP	4124RP
Length:	6 7/16"	6 19/32"
Width:	1 7/8"	2 11/32"
Height:	1 15/32"	1 17/32"
Weight:	2.15 lbs.	2.15 lbs.
Lead Length:	White, Black 10" (± 1") Blue 12" (± 1")	
Bottom Exit:	All Leads 8" (± 1")	
Can Colors:	White(4123RP, 4124RP) Black(4123RPBE, 4123RPBES) Black(4124RPBE, 4124RPBES)	
Qty/Carton:	20	

IMPORTANT Notes:

May Replace ULT Models **4123P**; 4123PBPE, and 4123PBES.

May Replace ULT Models 4124P; 4124PBPE, and 4124PBES.

Wiring Diagram change to be Consistent with other CF models.

Warranty:

Universal Lighting Technologies warrants to the purchaser that each electronic ballast will be free from defects in material or workmanship for a period of 24 months from date of manufacture when properly installed and under normal conditions of use. Call 1-800-BALLASTx800 for technical assistance.

Manufactured in North America

Ballast Case must be grounded.
Install in accordance with the
National Electrical Code.

