

4214P; 4214PBE; 4214PBES

APPLICATION and PERFORMANCE SPECIFICATION

Description: Magnetic ballast for (2) CFQ13W/GX23 or (2) CFT13W/GX23 Compact Fluorescent Lamps

- Line Voltage: 277vac +/-10%, 60Hz
- Series Lamp Operation
- Pre-Heat
- High Power Factor

Model	Line Volts	Input Watts	Nominal Line Amps	Starting Current(Amps)	Power Factor	Ballast Factor	Ballast Efficacy Factor	Harmonic Distortion		Crest Factor
								3rd	Total	
4214P	277	26	0.100	0.090	> .90	.85	3.27	<16%	< 20%	<1.7
4214PBE	277	26	0.100	0.090	> .90	.85	3.27	<16%	< 20%	<1.7
4214PBES	277	26	0.100	0.090	> .90	.85	3.27	<16%	< 20%	<1.7

Application and Performance Specification Information Subject to Change without Notification.

Performance:

- Meets ANSI Standard C82.11-1993
- Class P Thermally Protected

Safety:

- No PCB's
- UL listed
(Class P, Indoor and Type 1 Outdoor)
- CSA Certified

Application:

- Minimum Starting Temperature: 32° F, 0° C
- Maximum Case Temperature: 90° C
- Sound Rated: A
- Leads: BE - Bottom Exit
BES - Bottom Exit w/Studs (Studs 2" O.C.)

Physical Parameters

- Length: 6 19/32"
- Width: 2 11/32"
- Height: 1 17/32"
- Weight: 2.10 lbs.
- Lead Length: White, Black 11" (± 1")
Red, Blue 16" (± 1")
- Bottom Exit: All Leads 8" (± 1")
- Can Colors:
White(4214P)
Black(4214PBE, 4214PBES)
- Qty/Carton: 10

Warranty:

Universal Lighting Technologies, Inc., warrants to the purchaser that each magnetic ballast will be free from defects in material or workmanship for a period of 2 years from date of manufacture when properly installed and under normal conditions of use. Call 1-800-BALLAST x801 for technical assistance.

Manufactured in North America

**Ballast Case must be grounded.
Install in accordance with the
National Electrical Code.**

